

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 7

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11051)

-----

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 7 only, with brass cap mkd:

    |<sup>¼</sup>  
    |S 7  
    1928

from which

- A fir, 36" dia., bears N.22°E., 80 lks., mkd: ¼ S7 BT.
- A fir, 4" dia., bears N.86°E., 37 lks., mkd: ¼ S7 BT.

Obliterate old ¼ sec. cor. without taking a tie to it.  
The (1923) ¼ corner, by Mensch & Wilkes (Vol. 26 Pg 11143), established for secs. 7 & 12, H Raymond fd that there was an error on the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012