

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100596

PRIMARY CORNER DESCRIPTION East Cor. Secs. 1 & 12 only; T30-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11052)

Set an iron post, 3 ft. long, 2" dia., 30" in the ground for cor. of secs. 1 and 12 only, with brass cap mkd:

T30S		T30S
S 1		R3E
S 12		S 7
R 2 E		

1928

from which

A cedar, 18" dia., bears S.66°W., 66 lks., mkd: T30S R2E S12 BT.

A fir, 10" dia., bears N.63°W., 29 lks., mkd: T30S R2E S1 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11143), established for secs. 1, 6, 7 & 12, on line (S.0°13'W., 6.49 chs). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/7/2012