

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11119)

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 19}{S\ 30}$
1928

from which

- A fir, 36" dia., bears N.25°E., 47 lks., mkd: 1/4 S19 BT.
- A fir, 16" dia., bears S.13°E., 25 lks., mkd: 1/4 S30 BT.

Jackson Co. Surveyors Office - Kerry K Bradshaw, Co. Surveyor - H. Durkee & S. Fein - July 28, 2010 - C.S. File 65/77-24

Found - At the corner position, exposed 3", the 1" dia. galv. iron pipe with a 2 1/2" dia. brass cap set by the GLO in 1928, (properly) marked.

BTs by Raymond in 1928 fd with healed blazes and measured to center at base:

- W.Fir, now 55" dia. brs. record; N.25°E., 31.0 ft.
- S.Fir, now 25" dia. brs. S.14°E., 16.5 ft. Rec. S.13°E.

New - Mark new BTs "CS" "BT" and take measurements to center of trees at lower blaze:

- W.Fir 10" dia. brs. N.52°W., 17.0 ft.
- S.Fir 10" dia. brs. S.28 1/4°W., 9.8 ft.

Note - Corner lies approx. 2000 ft. westerly, then northerly along "Golden Stairs" Trail No. 23, from switchback in spur road to the county line; then, easterly approx. 300 ft.

V = 15°30'