

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias	Description

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11117)

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T30S R3E
S 19 | S 20
S 30 | S 29
1928

from which

- A hemlock, 10" dia., bears N.36°E., 41 lks., mkd: T30S R3E S20 BT.
- A fir, 14" dia., bears S.49½°E., 53 lks., mkd: T30S R3E S29 BT.
- A cedar, 18" dia., bears S.38°W., 93 lks., mkd: T30S R3E S30 BT.
- A fir, 20" dia., bears N.36½°W., 109 lks., mkd: T30S R3E S19 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Oct. 19, 1977 - C.S. File 65/77-25

Found - Lying on stump near re-establish position of corner, the orig. 1x36" iron pipe with attached GLO brass cap (properly) mkd. by H. Raymond in 1928.

I re-set said pipe 30" in ground, from which original BTs fd as follows:

Hemlock, 19" dia., with healed single blaze brs record; N.36°E., 27.06 ft. to center.

SE bearing tree is now gone.

Cedar, 17" dia., with healed single blaze, brs record; S.38°W., 61.38 ft. to center.

Fir snag, 18" dia., containing scribe mks, including "R3E S19 BT" in partially exposed face, brs. record; N.36½°W., 71.94 ft to center.

New - I mark new trees CS BT, and take measurements to center of trees at lower blaze:

Hemlock, 18" dia., brs. S.86¼°E., 97.18 ft.

Hemlock, 12" dia., brs. N.12½°W., 39.48 ft.

Note - Corner lies about 350 ft. west of logging road C.N-S, and near NW corner of clear-cut unit and 30 ft south of the top of small ridge C. N.80°E.

V = 19½°