

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. secs. 17, 18, 19, & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 26 Page(s) 11120)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 17, 18, 19, & 20, with brass cap mkd

T30S R3E  
S 18 | S 17  
S 19 | S 20  
1928

from which

- A fir, 24" dia., bears N.24°E., 39 lks., mkd: T30S R3E S17  
BT.
- A fir, 40" dia., bears S.52°E., 34 lks., mkd: T30S R3E S20  
BT.
- A fir, 30" dia., bears S.75°W., 61 lks., mkd: T30S R3E S19  
BT.
- A fir, 18" dia., bears N.3°W., 56 lks., mkd: T30S R3E S18  
BT.