

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 26 Page(s) 11126-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 5, 6, 7, & 8, with brass cap mkd

T30S R3E  
S 6 | S 5  
S 7 | S 8  
1928

from which

A fir, 36" dia., bears N.0°45'E., 5.59 lks., mkd: T30S R3E  
S5 BT.

A pine, 22" dia., bears N.6°30'W., 4.01 lks., mkd: T30S  
R3E S6 BT.

No other trees available, build a mound of stone, 4 ft. base,  
2½ ft. high, 78 lks. West of the cor.