

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11103)

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd

T30S R3E
S 20 | S 21
S 29 | S 28
1928

from which

- A cedar, 10" dia., bears N.54°E., 24 lks., mkd: T30S R3E S21 BT.
- A fir, 10" dia., bears S.82½°E., 81 lks., mkd: T30S R3E S28 BT.
- A cedar, 24" dia., bears S.35°W., 54 lks., mkd: T30S R3E S29 BT.
- A pine, 20" dia., bears N.43½°W., 69 lks., mkd: T30S R3E S20 BT.

Jackson Co. Surveyors Office - Roger R Roberts, Co. Surveyor - B. Berman & H. Durkee - July 28, 2008 - C.S. File 65/77-26

Found - At corner position exposed 2" in a mound of stones, the 2" dia. galv. iron pipe with a 2½" dia. brass cap set by the GLO in 1927 (properly) marked.

Orig. BTs by Herbert Raymond in 1927, found and measured to center at base:

- Fir snag with opened blaze revealing scribe marks "S28 BT" brs. record; S.82½°E., 53.5 ft.
- Cedar sawed rotted stump brs. rec. S.35°W., 35.6 ft.
- Pine sawed rotted stump brs. rec. N.43½°W., 45.5 ft.

New - Marked new BTs "CS" "BT" and measured to center at lower blaze:

- D.Fir 5" dia. brs. N.34½°E., 7.5 ft.
- D.Fir 6" dia. brs. S.21½°E., 16.1 ft.
- D.Fir 5" dia. brs. S.22°W., 19.6 ft.
- D.Fir 5" dia. brs. N.86¼°W., 26.3 ft.

Note - Corner lies approx 220 ft E of spur road in old burn V = 16°05'