

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11090)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 21, 22, 27, & 28, with brass cap mkd

T30S R3E  
S 21 | S 22  
S 28 | S 27  
1928

from which

- A fir, 16" dia., bears N.29°E., 34 lks., mkd: T30S R3E S22 BT.
- A fir, 6" dia., bears S.71°E., 17 lks., mkd: T30S R3E S27 BT.
- A fir, 24" dia., bears S.5½°W., 69 lks., mkd: T30S R3E S28 BT.
- A fir, 10" dia., bears N.81°W., 33 lks., mkd: T30S R3E S21 BT.

Jackson Co. Surveyors Office - Kerry K Bradshaw, Co. Surveyor - B. Berman & H Durkee - Aug. 25, 2009 - C.S. File 65/77-27

-----  
Found - At the corner position, exposed 7" the 1" dia. galv. iron pipe with a 2½" dia. brass cap set by the GLO in 1928 and (properly) marked:

Original BTs by H. Raymond in 1928 fd with healed blazes and measured to center at base;  
D.Fir now 24" dia. brs. record N.29°E., 22.4 ft.  
D.Fir now 15" dia. brs N.81°W., 21.3 ft rec. 21.8 ft  
D.Fir rotted remains brs. record S.71°E., 11.2 ft.  
D.Fir snag brs. record S.5½°W., 45.5 ft.

New - Marked new BTs "CS" "BT" and measured to center at lower blaze;

W.Fir 8" dia. brs. S.60¾°W., 41.1 ft.  
Hemlock 10" dia. brs. S.51°E., 44.5 ft.

Note - Corner lies approx. 500 ft. S.45°W., of curve in gravel road on a 45% slope.

V = 14°