

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11092-3)

Set an iron post, 3 ft. long, 2" dia., 12" in the ground, to bedrock, and build a mound of stone, 4 ft. base, 1½ ft. high, around the post, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd

T30S R3E
S 16 | S 15
S 21 | S 22
1928

from which

- A hemlock, 5" dia., bears N.67°E., 61 lks., mkd: T30S R3E S15 BT.
- A hemlock, 8" dia., bears S.4½°E., 76 lks., mkd: T30S R3E S22 BT.
- A fir, 48" dia., bears S.69°W., 8 lks., mkd: T30S R3E S21 BT.
- A pine, 20" dia., bears N.83°W., 77 lks., mkd: T30S R3E S16 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 23, 1978 - C.S. File 58/183-4

-
- Found - Projecting 12" in mound of stone, the orig. 2" dia., iron pipe with standard GLO brass cap properly mkd. by H. Raymond in 1928.
- Orig. Hemlock, 11" with healed single blaze, bears N.67°E., 39.83 ft. to center. (Rec. N.67°E., 40.26 ft.)
 - Orig. Hemlock, 17" with scribe marks visible in partially healed single face bears record S.4½°E., 50.16 ft. to center
 - Orig. Fir stub, 50" containing scribe marks including "S21 BT" in partially exposed face, bears record S.69°W., 5.28 ft. to center.
- Original NW BT now gone
- New - I mark new trees CS BT and take measurements to center of trees at lower blaze: Douglas Fir, 11" bears S.27°W., 52.60 ft.
- Hemlock, 11" bears N.69°W., 92.66 ft.
- Note - Corner lies near top of SE ridge, 55 ft. east of center of (under construction) road.