

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 26 Page(s) 11094-5)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T30S R3E  
S 9 | S 10  
S 16 | S 15  
1928

from which

- A fir, 6" dia., bears N.32°E., 23 lks., mkd: T30S R3E S10  
BT.
- A fir, 6" dia., bears S.65°E., 18 lks., mkd: T30S R3E S15  
BT.
- A fir, 32" dia., bears S.74°W., 40 lks., mkd: T30S R3E S16  
BT.
- A fir, 6" dia., bears N.27°W., 15 lks., mkd: T30S R3E S9  
BT.