

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4 and 33 & 34 T29-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 25 Page(s) 10782-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T29S R3E  
S 33|S 34  
S 4|S 3  
T30S  
1927

from which

- A fir, 28" dia., bears N.21°E., 52 lks., mkd: T29S R3E S34  
BT.
- A fir, 26" dia., bears S.84°E., 105 lks., mkd: T30S R3E S3  
BT.
- A cedar, 5" dia., bears S.76°W., 29 lks., mkd: T30S R3E S4  
BT.
- A fir, 16" dia., bears N.43°W., 78 lks., mkd: T29S R3E S33  
BT.