

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11093)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 15
S 22
1928

from which

- A fir, 7" dia., bears N.68°E., 59 lks., mkd: 1/4 S15 BT.
- A fir, 8" dia., bears S.71°E., 3 lks., mkd: 1/4 S22 BT.

Jackson Co. Surveyors Office - Roger R Roberts, Co. Surveyor - B. Berman & H Durkee - July 30, 2008 - C.S. File 65/77-28

Found - At corner position, exposed 6", the 2" dia. galv. iron pipe with a 2 1/2" dia. brass cap set by Raymond in 1928 (properly) marked.

Orig. BTs fd, both snags with healed blazes and measured to center at base:

Fir brs. N.68°E., 39.3 ft. Record; 38.3 ft.

Fir brs. S.71°E, 21.4 ft. Record; 2.0 ft.

New - Marked new bearing trees 'CS' 'BT' and measured to center at lower blaze:

Cedar 11" dia. brs. N.64 1/4°E., 33.2 ft.

D.Fir 13" dia. brs. S.45 1/2°E, 24.5 ft.

Yew 5" dia. brs. N.13 1/4°W., 6.7.

S.Pine 12" dia. brs. S.88 1/2°W., 59.0 ft.

Note - Corner lies approx. 500 ft. E of logging spur road.
V = 15°20'