

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 26 Page(s) 11079-80)

-----  
Set an iron post, 3 ft. long, 2" dia., 18" in the ground, in  
the ground, to bed rock, and build a mound of stone, 4 ft.  
base, 1 ft. high, around the post, for cor. of secs. 14, 15,  
22, & 23, with brass cap mkd

T30S R3E  
S 15 | S 14  
S 22 | S 23  
1928

from which

- A fir, 22" dia., bears N.51°E., 88 lks., mkd: T30S R3E S14  
BT.
- A fir, 16" dia., bears S.16°E., 38 lks., mkd: T30S R3E S23  
BT.
- A fir, 48" dia., bears S.21°W., 35 lks., mkd: T30S R3E S22  
BT.
- A fir, 34" dia., bears N.71°W., 24 lks., mkd: T30S R3E S15  
BT.