

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11083)

Set an iron post, 3 ft. long, 1" dia., 32" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 11
S 14
1928

from which

- A pine, 15" dia., bears N.7°W., 14 lks., mkd: 1/4 S11 BT.
- A fir, 24" dia., bears S.86 1/2°W., 84 lks., mkd: 1/4 S14 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 28, 1978 - C.S. File 58/183-3

Found - Projecting 2" the original 1" dia. iron pipe with standard GLO brass cap (properly) mkd as recorded by H.Raymond in 1928.

Original BTs fd. as follows:

Sawed fir stump, 46" dia., brs. S.86 1/2°W., 55.52 ft. to center. Record; S.86 1/2°W., 55.44 ft.

P.Pine, 19" dia., with healed single blaze, brs. N.7°W., 9.5 ft. to center. Rec: N.7°W., 9.24 ft

New - I marked a new tree CS BT:

D.Fir, 22" dia., brs. S.2 1/2°W., 23.1 ft. to center of tree at lower blaze.

Note - Corner lies approximately 1300 ft. West of location marker on 18" dia. White Fir alongside road.

V = 20°

Jackson Co. Surveyors Office - Kerry K Bradshaw, Co. Surveyor - B. Beeman & H Durkee - Aug. 10, 2009 - C.S. File 65/77-29

Found - At corner position, exposed 4", the 1" dia. galv. iron pipe with a 2 1/2" dia. brass cap set by the GLO in 1928 and marked:

Orig. BTs recorded by H. Raymond of the GLO in 1928 found with healed blazes and measured to center at base:

Fir rotted sawed stump with reversed scribe brs. record S.86 1/2°W., 55.5 ft.

P.Pine dead, down, and rotted, brs. record N.7°W., 9.5 ft. to center of stump hole

BT marked in 1978 fd with healed double blaze and measured to center at lower blaze;

D.Fir now 28" dia. brs. record S.2 1/2°W., 23.1 ft.

continued next page

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - Marked new bearing trees "CS" "BT" and measured to center at lower blaze:
D.Fir 8" dia. brs. S.68°E., 32.1 ft.
D.Fir 9" dia. brs. N.82°W., 10.1 ft.
D.Fir 45" dia. marked with 3 notches facing monument
brs. N.40½°E., 9.8 ft

Note - Corner lies approx. 1300 ft W of bend in gravel rd.
V = 15°15'