

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11069)

Set an iron post, 3 ft. long, 2" dia., 33" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd

T30S R3E
S 11|S 12
S 14|S 13
1928

from which

- A fir, 6" dia. bears N.11½°E., 55 lks mkd: T30S R3E S12 BT
- A pine, 6" dia. bears S.42°E., 23 lks mkd: T30S R3E S13 BT
- A cedar, 10" dia., bears S.2½°W., 111 lks., mkd: T30S R3E S14 BT.
- A fir, 14" dia., bears N.85°W., 111 lks., mkd: T30S R3E S11 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Nov. 14, 1977 - C.S. File 65/77-30

Found - Orig. 2" dia. iron pipe, projecting 5" with GLO brass cap (properly) mkd:

Orig. BTs by H.Raymond in 1928 fd. as follows:

- D.Fir, 24" dia. with healed single blaze, brs. N.10°E., 36.05 ft. to center. Record: N.11½°E., 36.30 ft.
- W.Pine snag, 17" dia., with healed single blaze, brs. S.42°E, 15.82 ft. to center. Record: S.42°E, 15.18 ft.
- Cedar, 22" dia., with healed single blaze, brs. S.1½°W., 73.85 ft. to center. Record: S.2½°W., 73.26 ft.
- W.Fir, 31" dia., with healed single blaze, brs. record; N.85°W, 73.26 ft. to center.

I mk a new tree CS BT:

Hemlock, 13" dia., brs. S.74°E., 19.90 ft. to center of tree at lower blaze.

Note - Corner lies at east edge of swampy brush field. Decl. 17½°

Jackson Co. Surveyors Office - Kerry K Bradshaw, Co. Surveyor - B. Berman & H. Durkee - Aug. 27, 2009 - C.S. File 65/77-30

Found - At the corner position, exposed 5", the 1" dia. galv. iron pipe with a 2½" dia. brass cap set by the GLO in 1928 and (properly) marked:
continued next page

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor Secs 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. BTs recorded by H. Raymond, GLO in 1928 fd
with healed blazes & measured to center at base;
D.Fir now 33" dia. brs. record N.10°E., 36.1 ft.
W.Pine dead and down brs record S.42°E., 15.8 to
center of stump hole.
Cedar now 31" dia. brs. record S.1½°W., 73.8 ft.
W.Fir snag brs. record N.85°W., 73.2 ft.
Mkd new BTs 'CS' 'BT' and measured to center at lower blaze;
W.Fir 7" dia. brs. N.23°W., 30.7 ft.
Note - Corner lies approx. 800 ft. westerly from gravel
road at northerly edge of swampy area.
Decl. 14°