

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11071)

Set an iron post, 3 ft. long, 1" dia., 18" in the ground, to bed rock, and build a mound of stone, 4 ft. base, 1 ft high, around the post, for ¼ sec. cor., with brass cap marked

¼
S 11|S 12
1928

from which

A fir, 24" dia., bears N.35½°E., 43 lks., mkd: ¼ S12 BT.

A fir, 36" dia., bears N.24½°W., 68 lks., mkd: ¼ S11 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 28, 1978 - C.S. File 58/183-2

Found - Projecting 3" in large mound of stone the original 1" dia. iron pipe with GLO brass cap (properly) mkd: Orig. BTs by H Raymond in 1928 fd. as follows:
Sawed fir stump, 28" dia. scribed "¼ S12 BT" in exposed face, brs. N39½°E, 29.30 ft. to center. Record; N.35½°E., 28.38 ft.
D.Fir, 39" dia., scribed "¼ S11 BT" brs. N.24½°W., 44.52 ft. Rec. N.24½°W., 44.88 ft.

I mk a new tree CS BT

D.Fir, 5" dia., brs. N.87°E., 20.20 ft to center of tree at lower blaze.

Decl. 19°