

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias	Description

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11071-2)

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T30S R3E
S 2 | S 1
S 11 | S 12
1928

from which

- A fir, 14" dia., bears N.52°30'E., 42 lks., mkd: T30S R3E S1 BT.
- A fir, 10" dia., bears S.24°30'E., 11 lks., mkd: T30S R3E S12 BT.
- A fir, 8" dia., bears S.52°15'W., 43 lks., mkd: T30S R3E S11 BT.
- A fir, 34" dia., bears N.25°30'W., 47 lks., mkd: T30S R3E S2 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 28, 1978 - C.S. File 58/183-1

Found - Projecting 5" the original 2" dia. iron pipe with standard GLO (properly) brass cap, mkd. as recorded by H. Raymond in 1928.

Orig. BTs fd as follows:

- W.Fir, 24" dia., with healed single blaze, brs. record; S.24½°E., 7.26 ft to center.
- W.Fir, 12" dia., with healed single blaze, brs. S.52½°W., 28.04 ft. to center. Record; S.52½°W, 28.38 ft

The original NE and NW BTs are now gone.

New - I mark new trees CS BT and take measurements to center of trees at lower blaze:

- Cedar, 9" dia., brs. N.30½°E., 39.3 ft.
- Chinquapin, 8" dia., brs. N.48°W., 28.52 ft.

Note - Corner lies near toe of SE slope, about 100 ft North of head of draw c. NE.