

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2 and 35 & 36 T29-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 25 Page(s) 10780)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 1, 2, 35, & 36, with brass cap mkd

T29S R3W  
S 35 | S 36  
S 2 | S 1  
T30S  
1927

from which

- A fir, 24" dia., bears N.43°E., 42 lks., mkd: T29S R3E S36  
BT.
- A pine, 48" dia., bears S.34°E., 47 lks., mkd: T30S R3E S1  
BT.
- A fir, 18" dia., bears S.12°W., 47 lks., mkd: T30S R3E S2  
BT.
- A fir, 32" dia., bears N.10°W., 31 lks., mkd: T29S R3E S35  
BT.