

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11059-60)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T30S  
R3E    R4E  
S 1 | S 6  
S 12 | S 7  
1927

from which

- A pine, 20" dia., bears N.33°E., 64 lks., mkd: T30S R4E S6 BT.
- A fir, 24" dia., bears S.41½°E., 44 lks., mkd: T30S R4E S7 BT.
- A fir, 18" dia., bears S.45°W., 72 lks., mkd: T30S R3E S12 BT.
- A fir, 18" dia., bears N.46½°W., 66 lks., mkd: T30S R3E S1 BT.

Jackson Co. Surveyors Office - Ed McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 14, 1978 - C.S. file 58/183-1

- Found - Flush with the ground, the orig. 2" iron pipe with standard 1927 GLO brass cap properly marked as recorded by H. Raymond.  
The single remaining BT, now a sawed fir stump, scribed "1 BT" in opened remaining portion of face, bears record N.46½°W., 43.56 ft. to center
- New - I marked new trees CS BT and take measurements to center of trees at lower blaze:  
27" D.Fir, bears N.19°E., 62.7 ft.  
17" Hemlock, bears S.67°E., 88.2 ft.  
39" D.Fir bears S.81°W. , 54.5 ft.  
24" W.Fir, bears N.20°W. , 6.0 ft.
- Note - Corner lies approx. 115 ft. west of trail along top of river (right) bank.

Jackson Co. Surveyors Office - Kerry K Bradshaw, Co. Surveyor - B. Berman & H. Durkee - Aug. 13, 2009 - C.S. file 65/77-32

- Found - At the corner position, flush, the 1 in. diam. galv. iron pipe with a 2½" dia. brass cap set by the GLO in 1927 and (properly) marked:  
BTs recorded on 1st re-establishment in 1978 fd with healed double blazes and measured to center at lower blaze; cont. next page

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T30-04E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

D.Fir now 35" dia. brs. N.20°E, 62.7 ft. record;  
N19°E.  
Hemlock now 24" dia. brs. record S.67°E., 88.2 ft.  
D.Fir now 46" dia. brs. record S.81°W., 54.5 ft.  
W.Fir snag brs. record N.20°W., 6.0 ft.  
New - Marked new BT 'CS' 'BT' and measured to center at  
lower blaze;  
W.Pine 32" dia. brs. N.31½°W., 112.5 ft.  
Note - Corner lies approx. 3100 ft. south-westerly along  
trail from Hwy 62 and then approx. 100 ft west.  
Dec. 16°15'