

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 039040

PRIMARY CORNER DESCRIPTION Interior NE Cor. Jacob Amsler DLC #39

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated June 8, 1857 - Page 617, DLC Volume

-----  
Set post interior cor. from which  
An Oak 15" dia., bears S.30°E., 48 lks.  
An Oak 18" dia., bears West 34 lks.

Douglas Co. Surveyor Office - Ben B. Irving, Deputy - Wit:  
J.A. Irving; V.N. Poole; Walter Poole; Roy Mathews - March 7-  
8, 1930 - C.S. File 37/18

-----  
Rock on upper side or road. Checks one original BT, down and  
rotting. 6" x 8" boulder X on top. From which  
A 14" Fir N.30°W., 26 lks. mkd. Int. Cor. Cl. 39 CS BT.  
A 12" Fir N.60°E., 46 lks. mkd. Int. Cor. Cl. 39 CS BT.  
See also M15-60 & C.S. File 43/6 for 1948 DCSO survey

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 2/24/1999 - C.S. File 66/12-5

-----  
Found - Boulder from 1930, not found. Corner lies in cut  
bank of new road construction.  
12" now 32" dia., D.Fir with bark scribing "INT COR  
CL 39 CS", bears N.60°E., 30.4 ft. 1930  
1930 NW BT now roothole found at rec. "N.30°W., 17.2  
ft."  
Set - 5/8" x30" long iron rod with DCSO alum cap stamped  
"INT DLC 39" is set at position determined from  
1930 BT. Protrudes 3" above ground.  
23" dia., D.Fir single blazed & scribed "INT DLC 39  
CS BT" bears N.28°W., 26.5 ft.  
4" dia., Madrone bark scribed "X CS BT" bears  
N.7°E., 24.5 ft.  
5/8" I.R. with yellow plastic cap marked "AA" bears  
N.50°W., 60.1 ft. (CS 660+99.93 70) R/W pin.  
Note - Corner lies 40 ft. North of  $\odot$  to highway within R/W  
cut bank.