

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6875)

Set ¼ sec. post, from which
 A B.Oak 14" dia., bears N.78°W., 145 lks. dist.
 A B.Oak 18" dia., bears S.85°E., 24 lks. dist.
Amely's house, S.55°W.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 16 Page(s) 6895-96)

¼ sec. cor. post is gone but both bearing trees are standing. I restore this cor. by setting a quartz rock, 12 x 10 x 6, 8" in the ground, mkd. ¼ on W. face, from which
 A B.Oak 14" dia., bears N.78°W., 145 lks. dist. mkd. ¼ S BT.
 A B.Oak 30" dia., bears S.85°E., 24 lks. dist. mkd. ¼ S BT.
I remark these trees, the old marks being dim, and overgrown.

Ben B. Irving, Deputy Co. Surveyor - Wit: John A. Irving; V.N. Poole; Joe Wright; Walter Poole - Feb. 18-19, 1930 - C.S. File 37/18 and M 1-37

Location identified to original BTs as recorded. One only a stump, the other dying. Set 4" x 4" x 36" Post for corner. Blazed and scribed:
 A Fir 22" dia. N.65°E., 63 lks.
 A Fir 30" dia. S.80°E., 80 lks. "S30 CS BT".

Ben B. Irving, County Surveyor - Arthur Evans; Milo Godfrey; Franklin D. Smith, crew - Nov/Dec. 1948 - C.S. File 43/6 and M 15-60

Location identified from original BTs:
 30" Fir S.80°E., 80 lks., alive, standing, scribe marks plain.
 22" Fir stump N.65°E., 63 lks., scribe marks visible.
Set 2½" x 36" I.P. for corner.
Blazed and scribed:
 12" Fir N.70°E., 38.0 ft. mkd. "¼ S30 CS BT".

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron and crew - Feb. 27, 1963 - C.S. File 52/138

Found - 12" now 20" Fir N.70°E., 38.0 ft. We open and find good scribing.
22" Fir stump N.65°E., 41.6 ft., shows bark scribe marks.
30" Fir stump S.84°E., (not S.80°E) 52.8 ft, shows scribe marks.

Do not find I.P. set at corner.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W
W 1/4 S30
1963

New BT - 15" R.Fir bears N.7°E., 22.6 ft. scribed W¼ S30 CS BT.

Corner is 70 ft. North of private road.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/18/1999 - C.S. File 66/8-15

Found - 2½" brass cap on a 1½" iron pipe, bent 1½ ft. southwest of plumb. 1963 . Monument straightened and surrounded by a 1½ ft. dia. mound of stone. Protrudes 13" above ground.

22"now 22" D.Fir stump rotted no scribing visible, bears N.65°E., 41.6 ft. 1930

12" now 27" dia. D.Fir with a fully healed double blaze, bears N.68°E., 37.0 ft. (rec. N.70°E., 38.0 ft.) 1948

15" now 32" dia. D.Fir with a fully healed double blaze, bears N.5°E., 21.6 ft. (rec. N.7°E., 22.6 ft.) 1963

New: 14" dia. D.Fir double blazed and scribed "W ¼ S30 CS BT" bears S.14½°W., 20.3 ft. note BT on wrong side of line.

Fd. Ok by Kristian DeGroot - 11/2006 - M146-49