

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6874)

Set ¼ sec. post, from which
A W.Oak 14" dia., bears N.30°W., 230 lks. dist.
A W.Oak 18" dia., bears N.2°E., 350 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 16 Page(s) 6898)

¼ sec. cor. post is gone, both bearing trees are standing and easily identified. I restore this cor. by setting a W.Oak post, 3 ft. long, 4" sq., 24" in the ground, mkd. ¼ S. on W. face, from which
A W.Oak 8" dia., bears N.74 3/4°E., 371 lks. dist. mkd. ¼ S BT.
A B.Oak 33" dia., bears S.31 3/4°W., 250 lks. dist. mkd. ¼ S BT.

Survey by Geo. J. Wenderoth - Aug. 1950/April 1951 - C.S. File 40/269

Set angle iron, from which
8" Oak, N.84°20'W., 66.7 ft.
3" Walnut N.17°24'W., 126.3 ft.

Douglas Co. Surveyors Office - Rod Kimberling & Mike Cline - 10/17/1977 (added 7/6/2016) - C.S. file 59/40-46

Reported as not found.
No monuments fd. Ran staff compass line from E¼ S24 T30S R4W, Wenderoth survey and searched with metal detector, but couldn't find angle iron. No accessories fd, nothing set.

BLM survey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133, surveyed June 1983/Dec. 1984 - (DCSO records Vol. 47 Page(s) 17850)

Point for the ¼ sec. cor. of sec. 19 only, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 30 S
R 4 W | R 3 W
| 1/4
| S 19
1983

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which
An Oak 44" dia., bears N.6°E., 467 lks. dist., mkd. ¼ S19 BT.
An Oak 17" dia., bears S.54½°E., 7½ lks. dist. mkd. ¼ S29 BT. From this point, a cor. established and recorded by Wenderoth in 1950-51, bears S.82°20'E., 1.087 chs. dist., determined from the remaining bearing tree mkd. by Wenderoth
An Oak 17" dia., bears N.84½°W., 101 lks. dist. with healed blaze.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18646)

¼ sec. cor. of sec. 19 only, monumented with a 1983 BLM brass cap from which the remains of bearing trees mkd. by Rogers, Bishop and White:
An Oak 44" dia., bears N.6°E., 467 lks. dist., with scribe marks ¼ S19 BT visible on open blaze.
An Oak snag 21" dia., bears S.54½°E., 7½ lks. dist. with scribe marks ¼ S19 BT visible on open blaze.
No other suitable trees available.

Fd. OK, Aug. 1992 by R. Brown - M 115-56