

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100353

PRIMARY CORNER DESCRIPTION C C for Secs. 13 and 24 only, T30-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William F. Briggs, U.S. Deputy Surveyor, under special instructions dated Aug. 7, 1891 - (DCSO records Vol. 17 Page(s) 7102)

Set B.Oak post 4½ ft. long, 4" sq., 24" in ground, for cor. to secs. 13 and 24. mkd. S13 on NW.; CC 3 notches on N. edge.; S24 SW CC 3 notches on S. edge, from which
A W.Oak 4" dia., bears N.10°W., 50 lks. dist. mkd. T30S R4W S13 CC BT.
A Fir 8" dia., bears S.60°W., 53 lks. dist. mkd. T30S R4W S24 CC BT.

Geo. J. Wenderoth - Wit: F. Sincomb - Aug. 1950 - M 24-79

Set by measurement and topography.
Truck axle for corner.
6" W.Oak N.22°15'E., 25.4 ft.
12" B.Oak S.46°35'W., 15.9 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - March 1963 - C.S. File 52/138-47

Found - Orig. 8" now 20" Fir stump S.60°W., 35.0 ft. We open near base and find good scribing "B".
Orig. NW. BT not found.

Set brass cap at cor. mkd. County Surveyors Office

CC	S13	T30S
R4W	S24	R3W
1963		

New BT - 10" R.Fir bears N.70½°W., 58.8 ft. scribed CC S13 T30S R4W CS BT.

Set ¾" I.R. West 25.4 ft. under N-S fence.

Corner is on steep South slope about 100 ft. North of small stream.

Corner as set by Wenderoth bears S.32°E., 81.2 ft. Wenderoth notified of change.

Wenderoth's and Byron's corners Fd. and tied in BLM survey by Rogers, Bishop and White, under Group #1133, surveyed June 1983/Dec. 1984 (DCSO records, Vol. 47 Pages 17850-51)

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18649-50) (and Pg. 18646)

(37.300 chs.)
(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100353

PRIMARY CORNER DESCRIPTION C C for Secs. 13 and 24 only, T30-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The original closing cor. of secs. 13 and 24, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with mdk. brass cap

from which the remains of an original bearing tree

A root hole bears S.60°W., 53 lks. dist.

and a reference monument and a bearing tree mkd. by Byron in 1963

An Iron rod, ¾" dia., firmly set, projecting 4" above ground, bears S.88°W., 39 lks. dist.

A burned Fir snag 17" dia., bears N.72½°W., 90 lks. dist. with healed blaze.

This corner now becomes an amended corner.

N.89°52'00"E., 37.335 chs.)

Intersect the W. bdy. of T.30S R3W., true point for the closing cor. of secs. 13 and 24.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 30 S

	R 4 W	R 3 W
C S 13		S 19
C S 24		
1988		

from which

A Madrone snag 8" dia., bears S.36°E., 53 lks. dist. mkd. T30S R4W S24 CC BT.

A Madrone snag 8" dia., bears N.1°W., 63 lks. dist. mkd. T30S R4W S13 CC BT.

There are no suitable live trees available due to the 1988 Bland Mountain fire.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. OK, Aug. 1992 by R. Brown - M 115-56