

PRIMARY CORNER DESCRIPTION AP on W. bdy. of Sec. 18

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6874)

Set ¼ sec. post, from which
A Lone B.Oak 10" dia., bears N.85°E., 62 lks. dist.
Made trench as per instructions.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 16 Page(s) 6899-6900)

¼ sec. cor. The post is gone, the old bearing tree is lying down, but showing the old marks plainly. I restore this cor. by setting a basalt rock 10 x 8 x 7, marked ¼ on W. face, in a mound of stone 3 ft. base and 2 ft. high on top of a bluff 25 ft. high, from which
A B.Oak 8" dia., bears N.85°E., 62 lks. dist. mkd. ¼ S BT
A B.Oak 4" dia., bears S.80°W., 5 lks. dist. mkd. ¼ S BT.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18648)

Point for the former ¼ sec. cor. of secs. 13 and 18, established by Ford in 1854, which is now an Angle Point, determined by the method of irregular boundaries, based on the Thiel resurvey; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

AP
T 30 S
R 4 W | R 3 W
S 13 | S 18
1988

from which
An Oak 6" dia., bears N.49°E., 26 lks. mkd. AP S18 BT.
A Fir 30" dia., bears N.31°W., 46 lks., mkd. AP S13 BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Surveying Tech., under Group No. 2000, 2100, 2300 - Surveyed Aug. 2005 - (DCSO records Vol. 55 Pages 21619 & 21620 and 2009-1 A&B BLM Plat)

An AP bet. secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½" dia., firmly set, projecting 8" above ground, in a mound of stone, 4 ft. base, with brass cop mkd. as reported by Rogers in 1988; cont.

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100432

PRIMARY CORNER DESCRIPTION AP on W. bdy. of Sec. 18

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

from which the remains of bearing trees mkd. by Rogers
A dead oak, 7" dia., bears N.49°E., 17.2 ft., with a
healed blaze.
A fir, 33" dia., bears N.31°W., 30.4 ft., with a healed
blaze.
and a new accessory
A rebar, 30" long, 5/8" dia., driven 28" in the ground as
a reference monument, bears N.75°E., 8.4 ft., with
aluminum cap mkd. RM T30S R3W S18 8.4 FT TO COR 2004,
and an arrow pointing to the cor.