

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100454

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only, T30-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William F. Briggs, U.S. Deputy Surveyor, under special instructions dated Aug. 7, 1891 - (DCSO records Vol. 17 Page(s) 7103)

Set W.Oak post, 4½ ft. long, 12" in ground, (struck bed rock), with rock mound 4 ft. at base, 18" high, for Cor. to Secs. 12 and 13, mkd. T30S R4W S12 C.C. NW., 2 notches on N. edge, S13 C C SW., 4 notches on S. edge, from which
A W.Oak 14" dia., bears S.79°W., 750 lks. dist. mkd. T30S R4W S13 CC BT.
A Red Fir 24" dia., bears N.5°W., 545 lks. dist. mkd. T30S R4W S12 C C BT.

Douglas Co. Surveyors Office - James Byron, Deputy - M. Godfrey and S. Bilow, crew - July 30, 1958 - C.S. 49/45-3

Found - Orig. 14" now 22" W.Oak S.79°W., 495.0 ft. I find good scribing "BT".

Fir stump, now 36" that checks bearing and distance for orig. NW. BT. Stump has been badly burned and partly rotted, no scribing found.

Set brass cap at corner mkd: County Surveyors Office

T 30 S
R4W R3W
C.C. $\frac{S 12}{S 13}$ | S 18
1958

New BT - 10" W.Oak bears S.41°W., 186.0 ft. scribed C.C. 13 T30S R4W CS BT.

Chisled + 3" high and B 0 on solid rock outcropping on vertical face 12" above ground. Exposed ledge 3' x 3' x 3' faces S.20°W., N.36°W., 23.0 ft. from corner.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18652-53)

(39.465 chs.)

The original closing cor. of secs. 12 and 13, perpetuated and recorded by Byron in 1958, monumented with an iron post, 1¼" dia., firmly set, projecting 18" above ground, with mkd. brass cap

from which a bearing tree and bearing object mkd. by Byron

An Oak 12" dia., bears S.40°W., 278 lks. dist. with fragmentary scribe marks visible on partially healed double blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100454

PRIMARY CORNER DESCRIPTION C C for Secs. 12 and 13 only, T30-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The chisel mark X on the face of a rock outcrop, 3 ft. high, 3 ft. wide, bears N.37 3/4°W., 34½ lks. dist. This corner now becomes an amended corner. (N.88°59'00"E., 39.575 chs.)

True point for the closing cor. of secs. 12 and 13. Seat a brass tablet, 3¼" dia., with a 3½" stem, in a drill hole, flush with top of exposed bedrock mkd. T 30 S

R 4 W	R 3 W
C S 12	S 18
C S 13	
1988	

from which

A Fir 8" dia., bears S.38 3/4°W., 235 lks. dist. mkd. T30S R4W S13 CC BT.

A rock outcrop, 8 ft. long, 3 ft. high, and 3 ft. wide, bears N.21 3/4°W., 44 lks. dist. mkd. X B0.

From this point, the angle point bet. secs. 13 and 18, bears S.0°16'00"W., 18.000 chs. dist.

Fd BLM BC in rock, 1 BT & 1958 DCS0 BC by David Edwards, 4/2007 - M152-75

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Surveying Tech., under Group No. 2000, 2100, 2300 - Surveyed Aug. 2005 - (DCS0 records Vol. 55 Pages 21619 & 21620 and 2009-1 A&B BLM Plat)

The closing cor. of secs. 12 and 13. monumented with a brass tablet, 3¼" dia., firmly set, cemented in a drill hole, flush with top of exposed bedrock, mkd. as reported by Rogers in 1988; from which the remains of on accessory mkd. by Rogers

A dead fir, 16" dia., bears S.38¾°W., 155.1 ft. with a healed blaze.

and new accessory

A rebar, 30" long, 5/8" dia. driven 29" in the ground as a reference monument, bears S.61°W., 7.5 ft., with aluminum cap mkd. T30S R4W RM S13 7.5 FT TO COR 2004, and an arrow pointing to the cor.

From this corner, the original closing cor. of secs. 12 and 13, reported by Rogers in 1988. monumented with an iron post. 1¼" dia., firmly set, projecting 8" above ground, bears S.88°59'W., 7.3 ft., w/BC mkd. as reported by Rogers in 1988; from which the remaining accessory reported by Rogers

A rock outcrop, 8 ft. long, 3 ft. high, 3 ft. wide, bears N.37¾°W., 22.8 ft. mkd. with a + chiseled into the rock Latitude 42°58'06.40"N Longitude 123°07'12.58"W (NAD 1983(91))