

PRIMARY CORNER DESCRIPTION AP on W. bdy. Sec. 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6873)

-
- Set a post, cor. of secs. 7, 12, 13 and 18, from which
- A Red Fir 12" dia., bears S.47°E., 14 lks. dist.
 - A Red Fir 14" dia., bears N.12°E., 17 lks. dist.
 - A Red Fir 12" dia., bears N.88°W., 34 lks. dist.
 - A Red Fir 18" dia., bears S.85°W., 41 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 - (DCSO records Vol. 16 Page(s) 6899) and (Pgs. 7036-37)

A practically decayed post, without marks is standing, also all the bearing trees. I restore the cor. by setting a basalt rock, 16 x 8 x 6, 12" in the ground, mkd. with 2 notches on N. and 4 notches on S. edges, from which

- A Fir 16" dia., bears N.15°E., 17 lks. dist. mkd. T30S R3W S7 BT.
- A Fir 14" dia., bears S.50°E., 14 lks. dist. mkd. T30S R3W S18 BT.
- A Fir 8" dia., bears S.4°W., 50 lks. dist. mkd. T30S R4W S13 BT.
- A Fir 14" dia., bears N.88°W., 34 lks. dist. mkd. T30S R4W S12 BT,

which I remark.

GLO survey by Wm. Bushey, Contract #620, June 17, 1893 - (DCSO records, Vol. 16 Page 6972) (and 6977)

The old cor. to secs. 7, 12, 13 and 18, which is a stone, 8 x 6 x 4" above ground, marked with 2 notches on N. and 4 notches on S. edges, from which

- A Fir 16" dia., bears N.15°E., 17 lks. dist. mkd. T30S R3W S7 BT.
- A Fir 4" dia., (14" now) bears S.50°E., 14 lks. dist. mkd. T30S R3W S18 BT.
- A Fir 8" dia., bears S.4°W., 50 lks. dist. mkd. T30S R4W S13 BT.
- A Fir 14" dia., bears N.88°W., 34 lks. dist. mkd. T30S R4W S12 BT.

As this is not a cor. to secs. 7 and 18, I destroy the marks on the two trees in these secs.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 100471

PRIMARY CORNER DESCRIPTION AP on W. bdy. Sec. 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by John Jelley, Cadastral Surveyor, under Contract #599, surveyed Sept. 1965 - (DCSO records Vol. 33 Page(s) 13903)

At the former cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., established by Ford in 1854, which became an angle point in 1893 when Bushey established the closing cor. of secs. 7 and 18, determined at record bearing and distance from the remaining original bearing trees:

The rotted remains of a Fir stump, size indeterminate bears N.15°E., 17 lks. dist.

The rotted remains of a Fir stump, size indeterminate, bears S.50°E., 14 lks. dist.

A sawed Fir stump 32" dia., bears N.88°W., 34 lks. dist., mkd. BT on partly opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 30 S T 30 S

AP
S 12 | S 18
R 4 W | R 3 W
1965

from which new bearing trees

A Fir 6" dia., bears S.17°E., 13 lks. mkd. AP S18 BT.

A Fir 6" dia., bears S.38°W., 21½ lks. mkd. AP S12 BT.

Cor. Fd. and tied in BLM survey by Wayne Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records, Vol. 49 Page 18648

Latitude 42°58'20.37"N

Longitude 123°07'08.30"W

(NAD 1927)

(added 6/25/2008)

Fd BC & 2 BTs by David Edwards, 4/2007 - M152-75