

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 140240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Arthur Boyer - April 3, 1937 - C.S. File 30/11

Stone, from which

10" Fir N.10°W., 58 lks.

14" Fir N.40°W., 185 lks.

See also M15-60 & C.S. File 43/6 for 1948 DCSO survey

Bruce Shaner, L.S. #430 - For: Roseburg Forest Products -
Feb. 1995 - M 119-52 - C.S. File 63/161-17-19

Found - 24" D.Fir stump with scribes "BT" and evidence of
old BT face. This BT was ~~N.20°W.~~, *N.40°W., 122.1
ft. from the corner Irving set so we replaced
corner at proper position from this stump.

Set A 2½" brass cap on a 1"x30" iron pipe, mkd:

T30S R3W

C¼ + S30

1995

RLS 430

New Bearing objects:

10" Cedar, scribed "C¼ S30 BT", bears N.22°E., 70.3'.

20" Cottonwood, scribed "C¼ S30 BT", bears N.82°W.,
12.3'.

6' steel fence post, bears North, 1.4'.

6' steel fence post, bears West, 1.4'.

Corner is on a North bank of a meander channel of S. Umpqua
River & corner is S.45°E., 60' from S. shoulder, paved
Tiller-Trail Highway.

*Per research 3/5/2024 JC DCSO