

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6878)

Set ¼ sec. post, from which
A Fir 30" dia., bears S.80°E., 39 lks. dist.
A Fir 30" dia., bears N.65°E., 55 lks. dist.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: John Irving; V.N. Poole; Joe Wright; Walter Poole - Feb. 18-19, 1927 - C.S. File 30/11

Location identified from both original BTs as recorded. NE. tree down.
Set a Fir post 4" sq., x 36" long for corner. Remarked original BT standing and
A Fir 14" dia., N.53°E., 65 lks. "¼ S19 CS BT".

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Wit: Arthur R. Evans, Deputy; Milo Godfrey; Franklin D. Smith - Nov/Dec. 1948 - C.S. File 43/6 and M 15-60

Reset corner by driving 2½" x 36" boiler tube. Identified from original BTs.
14" Fir N.53°E., 65 lks.
30" Fir S.80°E., 39 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - March 1963 - C.S. File 52/138-51

Found - Orig. 30" now 40" Fir stump, S.80°E., 25.7 ft., shows scar.
14" now 20" Fir N.53°E., 42.9 ft., shows scribing.
Iron pipe set at corner, not found.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W
¼ S 19
S 30
1963
New BT - 12" R.Fir bears S.44°W., 15.0 ft scribed ¼ S30 CS BT
Corner is on steep West slope 100 ft. West of draw.

Fd. and used in BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17858)

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & Plat 2008-1

The ¼ sec. cor. of secs. 19 & 30 monumented with an iron post, 1¼" dia., firmly set, projecting 14" above the ground, with brass cap mkd. as reported by Rogers, et al, in 1983-84; from which the remains of an orig. BT

A burnt & sawed fir stump, 27" dia., bears S.80°E., 25.7 ft. with no marks visible.
and remains of BTs reported by Rogers, et al

A burnt fir snag, 23" dia., bears N.54°E., 43.6 ft. with no marks visible.

A burnt fir snag, 7" dia, bears S.42°W., 15.2 ft. with no marks visible.
and new accessories

A rebar, 30" long, 5/8" dia., driven 27" in the ground for a reference monument, bears N.45°E., 7.50 ft. with aluminum cap mkd. RM ¼ S19 7.50 FT TO COR 2004 and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears S.45°E., 7.50 ft. with aluminum cap mkd. RM ¼ S30 7.50 FT TO COR 2004 and an arrow pointing to the cor.