

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 19

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

George J. Wenderoth, County Surveyor - Aug. 1950/April 1951 -
C.S. File 40/269

Angle Iron at corner, from which
12" Fir N.45°W., 25.5 ft.
12" Fir S.5°45'E., 8.1 ft.

BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17864)

Point for the center ¼ sec. cor. of sec.19, at intersection with the E. and W. center line.

Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd: T 30 S R 3 W
C 1/4
S 19
1983

from which

A Cedar 8" dia., bears S.3°W., 36 lks. dist. mkd. C¼ S19 BT.

A Fir 6" dia., bears N.2°W., 28½ lks. dist. mkd. C ¼ S19

From this point, a corner established and recorded by Wenderoth in 1950-51, bears S.23°58'E., 0.138 chs. dist., monumented with an angle iron 1¼" x ¼" firmly set, projecting 6" above ground, from which a bearing tree mkd. by Wenderoth

A Fir 17" dia., bears S.1½°E., 13 lks. dist., with healed double blaze.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & Plat 2008-1

The center ¼ sec. cor. of sec. 19 monumented with an alum. post, 2½" dia., firmly set, projecting 5" above the ground, with alum. cap mkd. as reported by Rogers, et al, in 1983-84; from which the remains of BTs mkd. by Rogers, Bishop, & White

A burnt & sawed cedar stump, 22" dia., bears S.3°W., 23.8 ft. with no marks visible.

A roothole, bears N.2°W., 18.8 ft. no trunk remains.
and new accessories

A rebar, 30" long, 5/8" dia., driven 27" in the ground for a reference monument, bears N.44½°E., 7.50 ft. with aluminum cap mkd. RM C¼ S19 7.50 FT TO COR 2004 and an arrow pointing to the cor.

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A rebar, 30" long, 5/8" dia., driven 27" in the ground for a reference monument, bears N.35½°W., 7.50 ft. with aluminum cap mkd. RM C¼ S19 7.50 FT TO COR 2004 and an arrow pointing to the cor.

From this corner a point reported by Roger, et al, bears S.23°58'E., 9.11 ft. monumented with an angle iron 1½x¼" firmly set, 2" below the surface of the ground, from which the remains of a BT reported by Rogers, et al

A burnt & sawed fir stump, 23" dia., bears S.1½°E., 8.6 ft. with no marks visible.