

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6879)

Set ¼ sec. post, from which
 An Oak 30" dia., bears N.15°E., 34 lks. dist.
 An Oak 18" dia., bears S.65°W., 32 lks. dist.

George J. Wenderoth - Aug. 1950 - C.S. File 45/91 and M 7-56A

20" Fir bears S.54°45'W., 74.7 ft.
 16" Fir bears N.66°45'W., 76.9 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - March 1963 - C.S. File 52/138-34

Found - 1½" x 1½" angle iron at corner.
 Now 24" Fir S.58°W., (not S.54°W.) 74.7 ft. shows scribing.
 Now 20" Fir N.64°W., (not N.66°W.) 76.9 ft., shows scar.
 New BTs- 18" R.Fir bears S.60°W., 42.3 ft. scribed ¼ S19 CSBT
 7" R.Fir bears N.24°W., 18.3 ft. scribed ¼ S18 CSBT

BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17862)

The ¼ sec. cor. reestablished and recorded by Wenderoth in 1950-51, and is accepted as the best available evidence of the position of the original corner, and perpetuated and recorded by Byron in 1963, monumented with an angle iron 1½ x ¼ ins., firmly set, projecting 12" above ground, from which the remains of bearing trees by Wenderoth:

A Fir 25" dia., bears S.56°W., 114 lks. dist., with healed blaze.

A sawed Fir stump 20" dia., bears N.65°W., 112 lks. dist., with healed blaze.

and bearing trees mkd. by Byron:

A Fir 22" dia., bears S.58½°W., 64 lks. dist., with healed blaze.

A Fir 11" dia., bears N.25°W., 28 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 ½" dia., 24" in the ground, with brass cap mkd:

T 30 S R 3 W
 1/4 S 18
 S 19
 1983

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Reset angle iron alongside iron post.
The corner is located 2 lks. S. of barbed wire fence,
extending E. and W.

From this point, the United States Geological Survey,
Triangulation Station "BLAND MTN", 1953, bears N.33°56'W.,
61.99 chs. dist., monumented with brass disk, 3¼" dia., set
in a boulder projecting 8" above ground, with top mkd. U.S.
Geological Survey 1953 Elevation Above Sea Level Bland Mtn
Bench Mark +.

Fd. OK, 1989 by Markham - M 101-53

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert
H. Browning, Surveying Tech. under Group #2000, 2100, & 2300,
surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s)
21501-4) & Plat 2008-1

The ¼ sec. cor. of secs. 18 & 19, monumented with an iron
post 2½" dia., firmly set, projecting 1" above the ground,
with brass cap mkd. as reported by Rogers, et al, in 1983-84;
from which the remains of the bTs reported by Rogers, et al

A roothole bears S.56°W., 75.2 ft. no trunk remains.

A burnt fir snag, 13" dia., bears S.58½°W., 42.2 ft. with
no marks visible.

A roothole bears N.25°W., 18.5 ft. no trunk remains.

A roothole bears N.65°W., 73.9 ft. no trunk remains.

and new accessories

A rebar, 30" long, 5/8" dia., driven 28" in the ground for
a reference monument, bears South, 7.50 ft. with
aluminum cap mkd. RM ¼ S19 7.50 FT TO COR 2004 and an
arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 28" in the ground for
a reference monument, bears East, 7.50 ft. with
aluminum cap mkd. RM ¼ S19 7.50 FT TO COR 2004 and an
arrow pointing to the cor.