

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Survey by Robert M. Thompson - Feb/April 1956 - C.S. File 42/173

Set at intersection of N-S and E-W centerlines.
Set a 1 1/4" Iron pipe, from which new trees:
15" Maple N.5°00 W., 7.0 ft.
9" Maple S.77°50'E., 31.7 ft.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #599, surveyed Sept. 1965 - (DCSO records Vol. 33 Page(s) 13914)

Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 30 S R 3 W
C 1/4 S 7
1965

from which
A Fir 11" dia., bears S.71°E., 46 lks. dist. mkd. C 1/4 S7 BT
A W.Fir 13" dia., bears S.41°W., 28 lks. dist. mkd. C 1/4 S7 BT.

From this point, a point established by Thompspon, Reg. Eng. in 1956, bears S.68°52'W., 1.28 chs. dist., monumented with an iron pipe 1 1/2" dia., firmly set, extending 8" above ground, from which bearing trees mkd. by Thompson:
A Maple 16" dia., bears N.5°W., 12 lks. dist. mkd. C 1/4 3683 BT on partly healed double blaze.
A Maple 12" dia., bears S.78°E., 48 lks. dist., with illegible scribe marks on partly healed double blaze.