

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6889)

Set ¼ sec. post, from which
An Oak 15" dia., bears S.87°E., 190 lks. dist.
An Oak 12" dia., bears N.87°E., 220 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6976)

The ¼ sec. cor. has been destroyed and witness trees also.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: Lew Smich; Louis Gilboa - May 24, 1928 - C.S. File 14/29

Set proportional measurement between section corners, a Flint rock 4" x 6" x 20" set 16" in ground, chiseled T on top and ¼ on North face, from which
A 6" W.Oak N.45°E., 8 lks.
A 12" W.Oak N.65°W., 11 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Feb. 1963 - C.S. File 52/138-23

Found - Stone at corner and both BTs as recorded by Irving. Now 16" W.Oak N.65°W., 7.3 ft., shows scribing. NE. BT fair condition. Corner is 7.0 ft. East and 1.0 ft. South of fence corner. Fences running E-W and North. Set brass cap alongside corner stone and mkd. County Surveyors Office 1963 South ¼ S6 T30S R3W. New BT - 10" W.Oak in clump, bears S.46°E., 5.0 ft. scribed ¼ S CS BT. Marks not found on corner stone.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #599, surveyed Sept. 1965 - (DCSO records Vol. 33 Page(s) 13909-10)

A point established by Irving in 1928 bears South, 0.04 chs. dist., monumented with a flint stone 20x6x4 ins., firmly set, extending 2" above ground, subsequently remonumented by Byron in 1963, with an iron post 1" dia., firmly set, extending 11" above ground with brass cap mkd. in 1963 from which bearing trees mkd. by Irving:
A W.Oak 7" dia., bears N.45°E., 8 lks. dist., with healed blaze.
(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A W.Oak 17" dia., bears N.65°W., 11 lks. dist., with illegible scribe marks on partly healed blaze. and a bearing tree mkd. by Byron:
A W.Oak 11" dia., bears S.46°E., 8 lks. dist. mkd. ¼ S CS BT on double blaze

Fd. OK, Oct. 1992 by R. Brown - M 112-62

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/15/2005 - C.S. File 67/10-44

Condition report only -
Found - 1965 DCSO BC projects 10" above ground.
10" now 14" W.Oak, fully healed double blaze visible on most Westerly trunk in clump of 3, bears S.57½°E., 6.3 ft. to center of root crown (rec. S.46°E., 5.0 ft.) 1963 BT
6" now 7" W.Oak, no marks visible, bears N.45°E., 5.3 ft. (agrees w/rec) 1928 BT
16" now 21" W.Oak, healed single blaze visible bears N.65°W., 7.3 ft. (agrees w/rec) 1928 BT
Note - 2 ft. South of E-W fence approx. 150' North of Days Creek Rd.
Decl. 16¾°E.