

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 160400

PRIMARY CORNER DESCRIPTION E. 1/16 Cor. bet. Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by George J. Wenderoth - Aug. 1950 - C.S. File 45/91 and M 7-56 A

Set Angle Iron, from which
24" Madrona bears N.49°W., 22.2 ft.
18" Madrona bears N.49°E., 19.1 ft.

BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17861-62)

The E. 1/16 cor., established and recorded by Wenderoth in 1950-51, and is accepted as the corner, monumented with an angle iron, 1¼ x ¼ ins., firmly set, projecting 8" above ground, from which the remains of bearing trees mkd. by Wenderoth:

- A Madrone snag 18" dia., bears N.47°E., 30½ lks. dist., with scribe marks T 6 S C BT visible on decayed blaze.
- A Madrone 18" dia., bears N.52°W., 33 lks. dist., with fragmentary scribe marks visible on decayed blaze.

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

E 1/16 $\frac{S 18}{S 19}$
1983

from which new bearing trees:

- A Fir 12" dia., bears N.75°E., 19 lks. dist., mkd. E 1/16 S18 BT.
- A Fir 17" dia., bears S.25½°E., 36 lks. dist., mkd. E 1/16 S19 BT.

Reset angle iron alongside iron post.