

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 8 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6974)

At point of intersection, Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for closing cor. to secs.7 and 8, marked CC T30S R3W on S.; S8 on E.; and S7 on W. faces, with 5 notches on E. and S. faces, from which
A Maple 6" dia., bears S.20½°E., 36 lks. dist. mkd. T30S R3W S8 BT.
A Fir 16" dia., bears S.35¼°W., 39 lks. dist., mkd. T30S R3W S7 BT.
A Fir 16" dia., bears N.7½°W., 28 lks. dist., mkd. T30S R3W C C S7 and 8 BT.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: Lew Smick; Louis Gilboa - March 24, 1928 - C.S. File 14/29

Location identified from original BTs as described in the original field notes. Set a 1" x 30" drill steel for corner with a 4" x 4" x 28" Maple post alongside scribed S7 S8 T30S R3W CS CC.

Survey by John H. Markham, Jr. - Wit: Fred Seymour; E.R. Sutton - March 1951 - C.S. File 40/302

Determined by O.B.T.s
A Fir stump 28" dia., bears S.38°W., 25.7 ft. dist.
A Fir 26" dia., bears N.7½°W., 15.5 ft.
I rescribe both O.B.T.s
At corner point, Set 1" x 24" iron pipe, from which
A Maple 5" dia., bears S.12°E., 13.0 ft. mkd. S8 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-30

Found - Drill steel at corner with 1" x 18" I.P. alongside. Orig. 16" now 24" Fir, N.7½°W., 18.5 ft., shows good scar and bark scribing.
Find stump of orig. SW. bearing tree.
New BT - 8" Maple bears S.2°W., 14.0 ft. scribed CC T30S R3W S7 CS BT.
E-W wire fence 9 ft. North.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 176600

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 8 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by John Jelley, Cadastral Surveyor, Group #599, surveyed Sept. 1965 - (DCSO records Vol. 33 Page(s) 13712)

(16.69 chs.)

The original closing cor. of secs. 7 and 8, perpetuated and recorded by Markham in 1951, monumented with an iron pipe, 1" dia., firmly set, extending 3" above ground, from which the remaining original bearing trees:

A sawed Fir stump 28" dia., bears S.35¼°W., 39 lks. dist., with healed blaze.

A Fir 24" dia., bears N.7½°W., 28 lks. dist., with healed blaze and scribe marks S6 BT on bark blaze.

and a bearing tree mkd. by Byron in 1963:

A Maple 8" dia., bears S.2°W., 21 lks. dist., mkd. CC T30S R3W S7 CS BT on double blaze.

(16.72 chs. N.0°55'E.)

Intersect the S. bdy. of sec. 6

True point for the closing cor. of secs. 7 and 8

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

S 6
S 7 | S 8
CC
T 30 S R 3 W
1965

from which

A Fir 16" dia., bears S.10°E., 77 lks. dist. mkd. T30S R3W S8 CC BT.

A Fir 4" dia., bears S.51°W., 56½ lks. dist. mkd. X BT.

Fd. OK by D. Edwards, Dec. 1999 - M133-66

Fd BC, IR & 2 BTs by G Nygren - 3/2019 - M175-38