

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6877)

-
- A Fir 18" dia., cor. secs. 29, 30, 31 and 32, from which
 - A Fir 9" dia., bears S.40°W., 5 lks. dist.
 - A Fir 15" dia., bears N.40°W., 10 lks. dist.
 - A Fir 18" dia., bears S.88°E., 35 lks. dist.
 - A Laurel 18" dia., bears N.85°E., 29 lks. dist.

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6967)

The Sec. cor., which is a Fir tree, 18" dia., mkd. T30S S29 on NE.; R3W S32 on SE.; S31 on SW.; and S30 on NW. faces, with 5 notches on E. and 1 notch on S. edges, from which

- A Laurel 18" dia., bears N.85°E., 29 lks. dist. mkd. T30S R3W S29 BT.
- A Fir 18" dia., bears S.88°E., 35 lks. dist. mkd. T30S R3W S32 BT.
- A Fir 9" dia., bears S.40°W., 5 lks. dist. mkd. T30S R3W S31 BT.
- A Fir 15" dia., bears N.40°W., 10 lks. dist. mkd. T30S R3W S31 BT.

The witness trees in secs. 29, 31 and 32 are broken off about 8 ft. above the ground, I therefore mark 3 new witness trees as follows:

- A Fir 11" dia., bears N.34°E., 22 lks. dist. mkd. T30S R3W S29 BT.
- A Fir 18" dia., bears S.41°E., 82 lks. dist. mkd. T30S R3W S32 BT.
- A Fir 10" dia., bears S.42°W., 47 lks. dist. mkd. T30S R3W S31 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - June 13, 1960 - C.S. File 42/392-59

-
- Determined by O.B.Ts:
- 24" Fir S.29°W., 63.0 ft.
 - 30" Fir S.70°E., 12.9 ft., found scribe.
 - 30" Fir N.54°E., 16.2 ft.
- At corner point, Set 3/4"x30" I.P., from which
- 5" Chinquapin S.26°W., 38.0 ft. mkd. S31 R3W BT.
 - 12" Laurel N.44°W., 17.3 ft. mkd. S30 T30S R3W BT.
 - 12" Laurel N.10°E., 25.2 ft. mkd. S29 T30S R3W BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31, and 32

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Randall Smith & Stephen Flause, crew - March 3, 1988 - C.S. File 62/50-14 (sketches in file)

Found - Original Corner, 1857 corner tree, 18" now 31" dia., with bark blazes found on the SW, SE, NW, and North side of tree. The North blaze shows 5 axe marks, the East side 3, and the South side, 2. We opened SE. and SW. blazes approx. 10" and found no scribing, face or burling. No scribing was found on any of the bark blazes.

1" inside dia. iron pipe, (Rec. 3/4") protruding 3" above ground per Markham. I.P. is East 69.8 ft. of original corner tree described above.

15" now 31" dia. D.Fir with a possible blaze. We opened and found burl but no scribing. Bears N.54°W., 6.6 ft. (Rec. N.40°W., 6.6 ft.) Due to large amount of decay in this tree and its leaning position, we are not able to make a thorough search for scribing. orig. BT.

18" now approx. 20" dia. badly rotted D.Fir, only very bottom of trunk and roots remain, no scribing or blazes found, bears S.88°E., 23.1 ft. (Orig. BT)

Possible remains of orig. NE. and SW. badly decayed BTs found at record bearing and distances.

11" now 12" dia. D.Fir 12 ft. high snag with a fully healed single blaze. We open and find scribing "R3W" bears N.34°E., 14.5 ft. (agrees with record - 1893 BT)

18" now 31" dia. D.Fir with a fully healed single blaze bears S.41°E., 54.1 ft. (agrees with record - 1893 BT)

10" now 12" dia. D.Fir 7 ft. high snag with a fully healed single blaze, bears S.42°W., 32.0 ft. (Rec. S.42°W., 31.0 ft. - 1893 BT)

Original corner tree is alive, no monuments set.

New BTs- 8" dia. Chinquapin with a pistol butt measurement taken to center of root crown, double blazed and scribed "T30S R3W S30 CS BT", bears N.30½°W., 24.5 ft.

26" dia. D.Fir, double blazed and scribed "T30S R3W S31 CS BT", bears S.28°W., 25.3 ft.

26" dia. D.Fir, bark blazed and scribed "T30S R3W S29 CS BT" bears N.12°E., 15.4 ft.

We could find no record of old BTs described as found by Markham. Iron pipe is 28 years old, may be an important point of survey. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31, and 32

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

See following condition report of Markham corner.
Found - 1" I.D. Iron pipe (Rec. 3/4" x 30"), firmly set and protruding approx. 3" above ground.
Orig. 1857 18" now 31" dia. corner tree bears West 69.8 ft.
24" now 28" dia. D.Fir with a fully healed single blaze, bears S.29°W., 63.0 ft. (agrees w/Markham rec.) Source unknown.
30" now 32" dia. D.Fir with a fully healed single blaze which was previously opened, We re-open and find possible pieces of scribing (approx. 90 years of overgrowth evident) bears S.70°E., 12.9 ft. (agrees w/Markham) Source unknown.
30" now 30" dia. D.Fir with a fully healed single blaze, bears N.54°E., 16.2 ft. (agrees w/Markham) Source unknown.
5" now 7" dia. Chinquapin in a partially healed double blaze with illegible scribe visible, bears S.26°W., 38.0 ft. (agrees with Markham, record)
12" now 14" dia. dead and down Madrone with bark scribing visible "3S 30S" bears N.44°W., 17.3 ft. (agrees with Markham record)
12" now 13" dia. Madrone with a partially healed double blaze, scribing visible "R3W BT", bears N.10°E., 25.2 ft. (agrees with Markham record)
No new monuments or BTs set for this corner. For information on original corner, see above described report. Iron pipe corner is apparently in error. We could find no record of old BTs as recorded by Markham. Iron pipe is 28 years old - may be an important point of survey.

Fd. Ok by Bruce Shaner, 2/95, M 119-52, C.S. 63/161-16

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCS0 records Vol. 57 Pgs 22519-20)

The cor. of secs. 29, 30, 31, and 32, perpetuated by Monrean, in 1988, occupied by a burnt fir snag, 33" dia., with burnt and decayed opened blazes on the SE. and SW. faces, no marks visible, from which the remains of an original bearing tree
A burnt and decayed fir stump, 34 ins. diam., bears N.59°W., 5.7 ft., with no marks visible. (Record; N.40°W., 6.6 ft.)
and the remains of a bearing tree mkd. by Bushey
A roothole bears S.42°W., 31.0 ft., with no trunk remains.
and bearing trees mkd. by Monrean
continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A fir, 27" dia., bears N.12¾°E., 15.6 ft., with a healed double blaze.

A fir, 28" dia., bears S.21¼°W., 25.4 ft., with a healed double blaze.

A chinquapin, 12" dia., bears N.32¼°W., 24.5 ft., with no marks visible on a decayed, partially healed blaze.

At the corner point

Sawed off the original fir snag, and drive a finned aluminum rod, 3/4" dia., 36" long, 32" into the center of the stump, with aluminum cap mkd.

T30S	R3W
S 30	S 29
S 31	S 32
2006	

from which

An iron rod, 30" long, 5/8" dia., driven 29" in the ground for a reference monument, bears S.52°49'29"E., 7.24 ft. with aluminum cap mkd. RM T30S R3W S32 7.2 FT. TO COR. 2006 and an arrow pointing to the cor.

An iron rod, 30" long, 5/8" dia., 28" in the ground for a reference monument, bears N.32°21'43"W., 7.65 ft. with aluminum cap mkd. RM T30S R3W S30 7.6 FT. TO COR. 2006 and an arrow pointing to the cor.

Deposit a magnet without its white plastic case alongside the finned aluminum rod.

From this cor., a point erroneously perpetuated as the cor. of sections 29, 30, 31, and 32, by Markham, in 1960, perpetuated and used in the subdivision of sec. 29, by McLind, in 1972, bears S.89°43'53" E., 70.03 ft., monumented with an iron pipe, 1" dia., firmly set, projecting 3" above the ground, from which bearing trees of unknown origin

A fir, 36" dia. bears N.53°E., 15.8 ft with a healed blaze

A burnt and sawed fir stump, 31" dia., bears S.71°E., 12.6 ft., with opened and decayed blaze and no marks visible.

and a bearing tree mkd. by Markham

A madrone, 16" dia., bears N.9°E., 24.4 ft., with partially healed blaze and no marks visible.

This point was established from bearing trees not of record, substantiated by Monrean, in 1988, and was not utilized in the course of this survey.