

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6877-78)

Set post, cor. secs. 19, 20, 29 and 30, from which
An Oak 9" dia., bears N.62½°W., 140 lks. dist.
An Oak 18" dia., bears S.8°W., 210 lks. dist.
An Oak 15" dia., bears S.64°E., 195 lks. dist.
An Oak 18" dia., bears N.1°E., 530 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Feb. 1963 - C.S. File 52/138-29

Found original 18" now 26" W.Oak S.8°W., 138.6 ft. Do not find scribing, center is rotted. Do find old axe work and it shows good scars. Ray Wright states that he saw Frank Cain open this BT at the time a survey was made, about 40 years ago for fence construction. Wright does not remember that this BT was scribed but he built the fence to South and to North on line and soon after survey. (Corner is 4.5 ft. North of fence corner)

New BTs- 5" Laurel bears N.82°E., 56.5 ft. scribed S20 CS BT.
12" W.Oak bears S.67°E., 60.5 ft. scribed S29 T30S R3W CS BT.
8" W.Oak bears N.48°W., 27.0 ft. scribed S19 T30S R3W CS BT.
6" Cedar bears S.48°W., 25.7 ft. scribed S30 T30S R3W CS BT.

BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17857)

The sec. cor. perpetuated and recorded by Byron in 1963, monumented with an iron post 1¼" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1963, from which the only remaining original bearing tree

A W.Oak 28" dia., bears S.8°W., 210 lks. dist., with axe marks visible on opened blaze.

and a bearing tree mkd. by Byron

A Cedar 20" dia., bears S.48°W., 39 lks. dist. with healed double blaze.

and new bearing trees

A Pine 8" dia., bears N.32°E., 134 lks. dist. mkd. T30S R3W S20 BT.

A Pine 12" dia., bears S.80°E., 202 lks. dist. mkd. T30S R3W S29 BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A Fir 18" dia., bears N.59½°W., 152 lks. dist. mkd. T30S R3W S19 BT.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & Plat 2008-1

The cor. of secs. 19, 20, 29 & 30, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above the ground, with brass cap mkd. as reported by Rogers, et at, in 1983-84; from which the remains of an orig. BT.

A burnt oak stump, 23" dia., bears S.8°W., 138.5 ft. with no marks visible.

and the remains of a BT reported by Rogers, et al

A root hole bears S.48°W., 25.7 ft. no trunk remains.

A root hole bears N.32°E., 88.4 ft. no trunk remains.

A root hole bears S.80°E., 133.3 ft. no trunk remains.

A burnt fir snag, 13" dia., bears N.59½°W., 100.3 ft. with no marks visible.

and new accessories

A rebar, 30" long, 5/8" dia., driven 27" in the ground for a reference monument, bears S.45°W., 7.50 ft. with aluminum cap mkd. RM T30S R3W S30 7.50 FT TO COR 2004 and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 27" in the ground for a reference monument, bears N.45°W., 7.50 ft. with aluminum cap mkd. RM T30S R3W S19 7.50 FT TO COR 2004 and an arrow pointing to the cor.

Fd. & used on BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22522-3)