

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6879)

Set post cor. secs. 17, 18, 19 and 20, from which
A Fir 15" dia., bears N.40°W., 73 lks. dist.
A Fir 18" dia., bears S.78°W., 68 lks. dist.
A Fir 24" dia., bears S.18°E., 14 lks. dist.
A Maple 6" dia., bears N.18°E., 66 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6961)

The Sec. cor., which is a post, greatly decayed, with marks nearly obliterated. I find the 4 original witness trees. At cor. point, I Set a stone 16x10x8 ins., 12" in the ground, marked with 5 notches on E. and 3 notches on S. edges, from which

A Maple 6" dia., (15" now) bears N.18°E., 66 lks. dist. mkd. T30S R3W S17 BT.
A Fir 24" dia., (28" now) bears S.18°E., 14 lks. dist. mkd. T30S R3W S20 BT. This tree is marked in the bark, I mark it in the wood "T30S R3W S20 BT"
A Fir 18" dia., (22" now) bears S.78°W., 68 lks. dist. mkd. T30S R3W S19 BT.
A Fir 15" dia., (20" now) bears N.40°W., 73 lks. dist. mkd. T30S R3W S18 BT.

George J. Wenderoth, Deputy Co. Surveyor - Wit: Francis Sincomb and Carl Hill - June 1950 - C.S. File 45/91 and M 7-56 A

Found all BTs:
36" Fir S.78°W., 44.9 ft., only one good.
18" Maple N.18°E., 43.5 ft., rescribe.
Drive 1" I.Pipe and mark
12" Fir N.27°45'W., 58.9 ft.
16" Cedar S.31°20'E., 42.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - March 1963 - C.S. File 52/138-34

Found - Iron pipe at corner and all BTs. NW. and SW. BTs now stumps.
New BT - 24" R.Fir bears S.44°W., 81.7 ft. scribed S19 T30S R3W CS BT.
No trees near to NW. Corner is under 36" log.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - J.H. Cook; P.L. Earle, crew - Jan. 22, 1976 - C.S. 59/2-12 & 18

Found - 1" dia. Iron pipe set in 1950. I.P. is firmly in place & approx. 36" dia. log lying over monument. Orig. 18" Fir, stump, now 36" dia., bears S.78°W., 44.9 ft. Blaze has been opened, scribing "BT" legible.

A Fir, uprooted and badly rotted, approx. standing position, bears S.18°E., 9.2 ft. Tree has scar which has been opened. No scribing visible.

A Maple 6" now 20" dia., bears N.19½°E., 43.6 ft. (Rec. N.18°E.) Tree blazed. Orig. blaze badly rotted, scribing "CS" legible from rescribe.

Orig. NW. BT not found.

A 12" now 13" Fir stump, badly rotted, bears N.28°W., 56.7 ft. (Rec. 58.8 ft.), scribing visible "18 CS BT".

A 16" now 26" dia. Red Cedar bears S.29°E., 42.0 ft. (Rec.S.31°20'E.) Tree has good blaze.

A 24" dia. Red Fir bears S.44°W., 80.8 ft. (Rec. 81.7 ft.) Tree has good blaze pitched over.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 3 W
S 18 | S 17
S 19 | S 20

1" Iron pipe alongside.

New BTs- 9" D.Fir bears N.58½°W., 51.5 ft. Tree blazed and scribed "T30S R3W S18 CS BT"

A 40" Red Fir bears N.48½°E., 48.1 ft. Tree blazed and scribed "T30S R3W S17 CS BT".

Fd. and used in BLM resurvey by Wayne Rogers; Lance Bishop; James White, Cad. Surveyors, under Group #1133 - Surveyed June 1983/Dec. 1984 - (DCSO records Vol. 47 Page(s) 17860-61)

(Corner is located 60 lks. West of and 15 ft. higher than a creek, 5 lks. wide, course S.25°E.)

BLM Dependent resurvey by Timothy Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1952, surveyed June. 2000. (DCSO rec. Vol. 53 page(s) 20712-3)

At the cor. of secs. 17, 18, 19, & 20, monumented with an iron pipe, 1½" dia., firmly set, projecting 4" above the ground, (alongside of which is an iron pipe, 1" dia., firmly set, projecting 11" above ground) with brass cap (properly) mkd. continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of original bearing trees
A maple, 20" dia., bears N.18°E., 43.6 ft., with a healed blaze.
A sawed burned and decayed fir stump, 37" dia., bears S.78°W., 44.9 ft., with a healed blaze.
and a bearing tree mkd. by Wenderoth
A cedar, 34" dia., bears S.31°E., 42.2 ft., with a healed blaze.
and the remains of a bearing tree mkd. by Byron
A sawed fir stump, 28" dia., bears S.43°W., 80.5 ft., with a healed blaze.
and the remains of a bearing tree mkd. by Monrean
A decayed fir snag, 49" dia., bears N.46°E., 47.5 ft., with a healed double blaze.
and a new bearing tree
A fir, 10" dia., bears S.70½°E., 78.6 ft., mkd. T30S R3W S20 BT.
There are no suitable trees within limits in sec. 17.

Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & Plat 2008-1

The cor. of secs. 17, 18, 19 & 20, monumented with an iron post, 1½" dia., firmly set, projecting 4" above the ground, with brass cap as reported by Rogers, et al, in 1983-84; from which the remains of orig. BTs
A burnt maple snag, 20" dia., bears N.18°E., 43.6 ft. with no marks visible.
A burnt, decayed & sawed fir stump, 32" dia., bears S.78°W., 44.9 ft. with a healed blaze.
and remains of BTs reported by Roger, et al
A burnt & decayed fir snag, size indeterminate, bears N.46°E., 47.5 ft. with no marks visible.
A cedar, 35" dia., bears S.31°E., 42.2 ft. with a healed blaze.
A burnt & sawed fir stump, 28" dia., bears S.43°W., 80.5 ft. with a healed blaze.
and the remains of a BT mkd. by Moore & Browning in 2000
A burnt fir snag, 10" dia., bears S.70½°E., 78.6 ft. with healed blaze.
and new accessories

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears S.45°W., 7.50 ft. with aluminum cap mkd. RM T30S R3W S19 7.50 FT TO COR 2004 and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears N.45°W., 7.50 ft. with aluminum cap mkd. RM T30S R3W S18 7.50 FT TO COR 2004 and an arrow pointing to the cor.

(NAD 1930 (91))

Latitude 42°58'02.93"N.

Longitude 123°06'03.33"W.