

PRIMARY CORNER DESCRIPTION Wit Cor to 1/4 Cor Secs 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6880)

Marked a Fir 15" dia., from which
A Fir 15" dia., bears S.40°E., 19 lks. dist.
A Fir 18" dia., bears S.30°W., 42 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6969-70)

The Cor. on the line between secs. 17 and 18, which is a Fir 15" dia., (20" dia. now) marked T30S R3W S18 on W. and T30S R3W S17 on E. faces, from which
A Fir 15" dia., bears N.40°E., 19 lks. dist. mkd. T30S R3W S17 BT.
A Fir 18" dia., (32" now) bears S.30°W., 42 lks. dist. mkd. T30S R3W S18 BT.

George J. Wenderoth - Aug. 1950 - C.S. File 45/91 and M 7-56A

Witness corner for ¼ corner is N.0°04'W., 300 ft. from the true corner. A 28" Fir, from which
18" Fir bears N.40°E., 12.5 ft.
32" Fir bears S.30°W., 18.5 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Feb. 1963 - C.S. File 52/138-28

Found - Stump of Corner tree, shows scribing.
Orig. 18" now 30" Fir, stump, S.15°W., (not S.30°W.) 27.7 ft., shows scribing.
Orig. 15" now 30" Fir, stump, S.28°E., 12.5 ft. (not N.40°E.), shows scar.
Set Brass cap 3.0 ft. South of center of Cor. tree and mkd:
County Surveyors Office
T 30 S R 3 W
W.C. S18 | S17
1963
New BTs- 4" R.Fir bears S.38°E., 4.0 ft. scribed W.C. S17 CS BT.
5" R.Fir bears N.77°W., 19.0 ft. scribed W.C. S18 CS BT.

continued next page

PRIMARY CORNER DESCRIPTION Wit Cor to 1/4 Cor Secs 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Timothy Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1952, surveyed June. 2000. (DCSO rec. Vol. 53 page(s) 20714-5)

The original line tree, a decayed fir stump, 28" diam., with illegible reverse scribing visible, perpetuated by Wenderoth, in 1950, further perpetuated by Byron, in 1963. This now becomes an Angle Point, from which the remains of the original bearing trees.

A decayed fir stump, 28" dia., bears S.26 $\frac{3}{4}$ °E., 12.5 ft., with scribe marks T30S R3W S17 visible on partially opened blaze. (Record, N.40°E.)

A decayed fir stump, 37" dia., bears S.12 $\frac{3}{4}$ °W., 27.6 ft., with scribe marks T30SR3WS18 visible on partially opened blaze. (Record, S.30°W.)

and accessories mkd. by Byron

An iron pipe, 1 $\frac{1}{4}$ " dia., firmly set projecting 16" above the ground for a reference monument, bears S.1°09'22"W., 2.27 ft., with brass cap mkd. COUNTY SURVEYORS OFFICE T30S S18 S17 R3W WIT COR 1963.

A decayed fir snag, 7" dia., bears S.24 $\frac{3}{4}$ °E., 5.9 ft., with no marks visible.

A fir, 9" dia., bears N.83 $\frac{1}{2}$ °W., 19.1 ft., with a healed double blaze.

At the corner point.

Set a finned aluminum rod, $\frac{3}{4}$ " dia., 92" in the ground, through the center of sawed off remains of the decayed line tree, with aluminum cap mkd. T 30 S R 3 W

AP
S 18 | S 17
2000