

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 238100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, T31-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7774)

-----  
At point of intersection, Set a stone 20x8x8 ins., 15" in the ground for closing cor. to secs. 5 and 6, marked C C on S. with 5 notches on E. and 1 notch on W. faces; from which  
A Fir 22" dia., bears S.64¼°E., 28 lks. dist. mkd. T31S R3W S5 BT.  
A Maple 8" dia., bears S.33°W., 24 lks. dist. mkd. T31S R3W S6 BT.  
A Laurel 10" dia., bears N.30°W., 10¼ lks. dist. mkd. T31S R3W C C S5 and 6 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Jan. 16, 1959 - C.S. File 42/392-10

-----  
Determined by O.B.T.s:  
30" Fir bears S.64°E., 18.5 ft.  
10" Maple bears S.33°W., 18.5 ft.  
At corner point, Set 1½" x 36" Iron pipe, from which  
7" Live Oak bears S.19°W., 70.0 ft. mkd. S6 BT.  
18" Fir bears N.54°E., 23.0 ft. mkd. S32 BT.  
16" Fir bears S.78°W., 15.0 ft. mkd. S6 X BT.  
So. ¼ corner Sec. 32 bears East 167.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1966 - C.S. File 52/63-40

-----  
Found - Iron pipe at sec. corner.  
Orig. 30" now 30" Fir S.64°E., 18.5 ft., shows good scar.  
Orig. 10" Maple S.33°W., 18.5 ft., partly rotted but still standing.  
7" Live Oak now 14" S.19°W., 70.0 ft. scribed S6 BT.  
18" Fir now 18" N.54°E., 23.0 ft. scribed BT S32.  
16" Fir now 18" S.78°W., 15.0 ft. shows good scar and "BT."

Set Brass cap alongside iron pipe and marked:

County Surveyors Office  
T 30 S R 3 W  
S 32  
-----  
S 6 | S 5  
T 31 S R 3 W  
1966

All trees in good condition. Best way to corner, walk up ravine until you come to E-W line, the East uphill.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 238100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, T31-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol 48 Pages 18336-37)

(59.40 chs.)

The original closing cor. of secs. 5 and 6, perpetuated and recorded by Markham in 1959, and further perpetuated and recorded by Powell in 1966, monumented with an iron pipe 1½" dia., firmly set, projecting 4" above ground, alongside is an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap mkd. in 1966, from which the original bearing trees:

A Fir 35" dia., bears S.57½°E., 24 lks. dist. with healed blaze. (Rec. S.64½°E., 28 lks.)

A Maple 14" dia., bears S.37½°W., 28 lks. dist. with rotted blaze, no marks visible. (Rec. S.33°W., 24 lks.)

and bearing trees mkd. by Markham:

A Fir 25" dia., bears N.75°E., 32 lks., with healed blaze.

A Live Oak 13" dia., bears S.19½°W., 106 lks. with healed blaze.

A Fir 22" dia., bears S.77½°W., 23 lks. with healed blaze.

(59.44 chs. N.0°23'W.)

Point for the closing cor. of secs. 5 and 6, at intersection with the S. bdy. of T30S R3W.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 30 S R 3 W  
S 32  
S 6 | S 5  
C C  
T 31 S R 3 W  
1986

No suitable trees available.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the ¼ sec. cor. of sec. 32 only, T30S R3W, bears N.89°22'E., 2.33 chs. dist.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Pages 22511-2)

The closing cor. of secs. 5 & 6 only, on the S bdy of the Tp. monumented with a stainless steel post 2½" dia. firmly set projecting 3" above the ground, with brass cap (properly) mkd There are no bearing trees available within limits.

From this point, the original closing cor. of secs. 5 & 6 only, bears S.6°48'33"W., 2.60 ft., monumented with an iron pipe, 1¼" dia. loosely set, projecting 22" above the cont.

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 238100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

ground, (alongside of which is an iron pipe, 1½" dia., firmly set, projecting 5" above the ground, set by Markham, in 1959, with brass cap (properly) mkd.  
from which the remains of original bearing trees  
A fir, 35" dia., bears S.57½°E., 15.8 ft., with a healed double blaze.  
A hollowed broken top maple, 16" dia., bears S.37½°W., 18.5 ft., no marks visible.  
and bearing trees mkd. by Markham  
A fir, 28" dia., bears N.75°E., 21.1 ft., with a healed blaze.  
A live oak, 15" dia., bears S.19½°W., 70.0 ft., no marks visible.  
A fir, 27" dia., bears S.77½°W., 15.2 ft., with a healed blaze.