

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6780) and (duplicate info. on page 6912)

-----  
Set a stone 12x12x8 ins., 8" in the ground for ¼ sec. cor. marked ¼ on N. face, from which  
A Fir 30" dia., bears N.71½°E., 15½ lks. dist. mkd. ¼ S BT  
A Live Oak 10" dia., bears S.15°W., 47½ lks. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Jan. 16, 1959 - C.S. File 42/392-9

-----  
Determined by O.B.T.s:  
36" Fir bears N.71°E., 10.2 ft.  
10" L. O. stump bears S.15°W., 31.2 ft., found scribe.  
At corner point, SET 1½" x 30" Iron pipe, from which  
9" Laurel bears N.50°E., 52.0 ft. mkd. ¼ S32 X BT.  
10" Live Oak bears S.46°E., 41.0 ft. mkd. ¼ S32 BT.  
23" Fir bears S.7°E., 38.0 ft. mkd. ¼ S32 BT.  
Sec. cor. for 5 & 6, T31-3 bears West 167.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-41

-----  
Found - Iron pipe at ¼ corner.  
Orig. 36" D.Fir N.71°E., 10.0 ft., shows good scar.  
9" Laurel now 11" N.50°E., 52.0 ft., should be 48.8 ft., scribed ¼ S32 BT.  
10" Live Oak now 13" S.46°E., 41.0 ft., should be 34.4 ft., scribed ¼ S32 BT.  
23" D.Fir now 25" S.7°E., 38.0 ft., bark scribed ¼ S32 BT.

Set brass cap alongside iron pipe at ¼ corner marked:

County Surveyors Office

T 30 S R 3 W

¼ S 32

T 31 S R 3 W

1966

All trees in good condition.

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18321)

-----  
The ¼ sec. cor., perpetuated and recorded by Markham in 1959, and further perpetuated and recorded by Powell in 1965, monumented with an iron pipe, 1½" dia., firmly set,  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 32 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

projecting 10" above ground, alongside is an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1965, from which the remains of an original bearing tree:

A Fir snag 30" dia., bears N.71½°E., 15½ lks. dist., with healed blaze.

and bearing trees mkd. by Markham:

A Madrone 14" dia., bears N.45½°E., 71 lks. dist., with healed blaze.

A double Live Oak 14" dia., bears S.44 3/4°E., 50 lks. dist., with healed double blaze.

A Fir 27" dia., bears S.6¼°E., 55 lks. dist. with scribe marks ¼ S32 visible on partially healed blaze.

and a new bearing tree:

A Cedar 12" dia., bears N.21½°W., 42 lks. dist., mkd. ¼ S32 BT.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Pages 22510-1)

-----  
The ¼ sec. cor. of sec. 32 only, on the S. bdy. of the Tp., monumented with an iron post, 1½" dia. firmly set, projecting 6" above the ground (alongside of which is the original stone, projecting 3" above the ground, with the marks ¼ visible, and an iron pipe, 1½" dia., firmly set, projecting 6" above the ground), with brass cap (properly) mkd.

from which the remains of original bearing trees

A sawed and burnt fir stump, 24" dia., bears N.71½°E., 10.2 ft., with no marks visible.

A roothole bears S.15°W., 31.4 ft., with no trunk remains. and the remains of bearing trees mkd. by Markham, in 1959

A live oak, 15" dia., bears S.44¾°E., 33.0 ft., with a healed blaze.

A fir, 25" dia., bears S.6¼°E., 36.3 ft., with a healed blaze.

and a bearing tree mkd. by Peterson and Bedell, in 1985-86

A cedar, 15" dia., bears N.21½°W., 27.7 ft., with fragmentary scribe marks visible on a partially healed blaze.