

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6881)

-----  
Set 1/4 sec. post, from which  
A Fir 30" dia., bears S.60°W., 16 lks. dist.  
A Fir 10" dia., bears N.55°E., 10 lks. dist.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Geo. Baughn and Dennis Vaughn - Jan. 26, 1951 - C.S. 40/384-3

-----  
Determined by O.B.T.  
A dead Fir snag 50" dia., bears S.60°W., 10.5 ft. dist.  
At corner point, Set 3/8 x 30" Iron rod, from which  
A Maple 10" dia., bears N.23°W., 31.0 ft. mkd. 1/4S S20 BT.  
A Yew 8" dia., bears S.2°E., 31.0 ft. mkd. 1/4S S29 BT.

Fd. and used corner per Markham, April 1987 - M 104-25

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22525)

-----  
The 1/4 sec. cor. of secs. 20 and 29, perpetuated by Markham, in 1951, monumented with an iron pipe, 1/2" dia., firmly set, projecting 6" above the ground, from which the remains of an original bearing tree  
A roothole bears S.60°W., 10.6 ft., with no trunk remains. and the remains of bearing trees mkd. by Markham  
A roothole bears S.2°E., 32.2 ft., with no trunk remains.  
A burnt maple stump, 24" dia., bears N.24 1/4°W., 31.0 ft. with no marks visible.

At the corner point  
Set a stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, directly over the iron pipe, with brass cap mkd.

T30S R3W  
1/4 S 20  
S 29  
2006

from which  
An iron rod, 30" long, 5/8" dia., driven 30" in the ground for a reference monument, bears N.37°16'50"E., 10.00 ft. with aluminum cap mkd. RM T30S R3W 1/4 S20 10.0 FT TO COR 2006 and an arrow pointing to the cor.  
An iron rod, 30" long, 5/8" dia., driven 30" in the ground for a reference monument, bears S.52°59'38"E., 8.00 ft. with aluminum cap mkd. RM T30S R3W 1/4 S29 8.0 FT TO COR 2006 and an arrow pointing to the cor.