

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6962)

A Fir 10" dia., which I mark $\frac{1}{4}$ S. on N. face, for $\frac{1}{4}$ sec. cor., from which

A Laurel 18" dia., bears S.12 $\frac{1}{4}$ °W., 23 $\frac{1}{2}$ lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 8" dia., bears N.30 $\frac{1}{2}$ °E., 29 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by John H. Markham, Jr. - May 1952 - C.S. File 41/52-2

Set from O.B.T.

14" Fir bears N.28°E., 19.0 ft. fd scribe.

Laurel stump bears S.15°W., 15.2 ft. fd old scribe.

At corner, found stump hole and down tree with scribe marks.

Set $\frac{3}{4}$ " x 14" Iron pipe, from which

14" Chinquapin bears S.37°W., 21.8 ft. mkd. $\frac{1}{4}$ S20 BT

Laurel 24" dia., bears N.32°E., 39.0' mkd $\frac{1}{4}$ S17 T30S R3W
2880 BT

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - March 1963 - C.S. File 52/138-35

Found - I.Pipe at corner.

Orig. 8" now 20" Fir snag N.30°E., 19.0 ft., shows scribing.

Now 16" Chinquapin S.37°W., 21.8 ft., shows scribing.

Now 36" Laurel bears N.31°E., 40.5 ft., shows bark scribing above and wood scribe "BT". This BT rescribed by Markham. We rescribe " $\frac{1}{4}$ S17 CS"

Set brass cap alongside corner I.P., mkd:

County Surveyors Office

$\frac{1}{4}$ S 17 T30S

S 20 R3W

1963

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & Plat 2008-1

The $\frac{1}{4}$ sec. cor. of secs. 17 & 20 perpetuated by Markham in 1952, further permutated by Byron in 1963, monumented with an iron post, 1 $\frac{1}{4}$ " dia., firmly set, projecting 8" above the ground) with brass cap (properly) mkd., from which the remains of the orig. BTs

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burnt fir stump, size indeterminate, bears N.30½°E., 19.1 ft. with no marks visible.
A root hole bears S.12¼°W., 15.5 ft. no trunk remains. and the remains of a BT mkd. by Markham
A roothole bears S.37°W., 21.8 ft. no trunk remains. and the remains of a BT reported by Byron as having been mkd. by Markham (there is no record Markham mkd this tree)
A burnt madrone snag, 15" dia., bears N.32¼°E., 40.5 ft. with no marks visible.
and new accessories
A rebar, 30" long, 5/8" dia., driven 27" in the ground for a reference monument, bears N.45°E., 7.50 ft. with aluminum cap mkd. RM ¼ S17 7.50 FT TO COR 2004 and an arrow pointing to the cor.
A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears S.45°E., 7.50 ft. with aluminum cap mkd. RM ¼ S20 7.50 FT TO COR 2004 and an arrow pointing to the cor.