

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6971)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S. on N. face, from which

A Fir 5" dia., bears S.51°E., 30 1/2 lks. dist. mkd. 1/4 S BT

A Fir 7" dia., bears N.62 1/2°E., 30 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Feb. 1963 - C.S. File 52/138-22

Found - Orig. 5" now 17" R.Fir, S.51°E., 20.2 ft. We open and find good scribing "S".

Orig. 7" now 14" Fir, N.62 1/2°E., 19.8 ft., down.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 3 W

1/4 S 8
S 17

1963

New BTs- Rescribe now 17" R.Fir S.51°E. 20.2 ft "1/4 S17 CS BT"
10" R.Fir bears N.43°W., scribed "1/4 S8 CS BT"

Troy Rambo - For: Seneca Jones Timber Co. - 9/2007 - M154-22

Found - 1963 DCSO brass cap, bent & record BTs per 1963 ren.
New - 10" DF bears S.24°W., 20.8 ft., scribed "1/4 S17 BT",
measured to a 6" spike at side center base, with
a hand compass, decl. of 17°E.

A new BT to the East was not added due to a very active yellow jacket nest.

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

Found - 2 1/2" brass cap stamped County Surveyor Office 1963
BTs - 11" Fir with tag dated 9/07 S.24°W., 20.8' to nail
side center

29" Fir with BLM tag dated 9/63 N.43°W., - 40.3' to
nail side center