

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6891)

Set ¼ sec. post, from which
A Fir 18" dia., bears S.10°E., 15 lks. dist.
A Laurel 10" dia., bears N.74°W., 33 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Feb. 1963 - C.S. File 52/138-27

Found - Orig. 18" now 24" Fir stump, S.10°E., 9.9 ft., shows old burned face and small bottom section of old axed face. No scribing.
NW. bearing tree not found.
Find 1" Iron bolt at corner.

Statement: I, T.F. Epping, state that I have seen scribing on the stump used on this date to establish the position of the South ¼ corner, Sec. 5, T30S R3W. Also, that the iron bolt found at this corner was set under my direction.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W
So. ¼ S5
1963

New BTs- 37" R.Fir bears N.15°E., 43.7 ft. scribed S¼ S5 CS BT. (Log at base of BT scribed 5.0 ft. above ground.)

11" R.Fir bears East 47.6 ft. scribed S¼ S5 CS BT.

Fd. OK by D. Edwards, Dec. 1999 - M133-66

James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-45 A-H

Found - 2½" brass cap stamped Co. Surveyors Office 1963
43" Fir snag 40' tall with healed face and tag dated 2/63, N.15°E., 43.7'
22" Fir with healed face and tag dated 2/63, N.89°E., 47.6'