

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; and 32 of T29-3

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6300)

Set ¼ sec. post, from which
An Oak 12" dia., bears S.88½°E., 320 lks.
An Oak 15" dia., bears N.82°E., 270 lks.

Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6318)

C.W. Springer, Deputy Co. Surveyor - Wit: N.E. Richardson; Thomas Hatfield - Oct. 20, 1923 ("Old" corner book, page 120) See also, Vol. 3 Pg. 169; C.S. File 6/29

Reestablished from stump of an Oak, 15" dia., N.82°E., 270 lks. and from Mr. R. Fates' testimony that his fence ran between the witness trees.
Drove an Iron pin, 3/4" x 24" in ground and set a Cedar stake 4"x4"x36" also, from which
A 22" Fir bears S.45°E., 13.7 ft.
A 24" Fir bears N.60°30'E., 43.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy and crew - Nov. 26, 1962 - C.S. File 52/126-79

Found 3/4" Iron bolt at corner and both BTs as recorded. Each shows good bark scribing.
New BT - 10" Cedar bears N.19°E., 18.4 ft. scribed ¼ S32 CS BT.

Fd. OK, Oct. 1992 by G. Lang - M 117-2

Fd. OK, Oct. 1993 by M. Hull - M 118-4