

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6880)

-----  
Set post cor. secs. 28, 29, 32 and 33, from which  
A Fir 18" dia., bears S.70°W., 30 lks. dist.  
A Laurel 10" dia., bears N.68°W., 46 lks. dist.  
A Laurel 10" dia., bears S.35°E., 42 lks. dist.  
An Oak 12" dia., bears N.60°E., 58 lks. dist.

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6955)

-----  
The sec. cor. post is gone. I find 3 of the original witness trees. At cor. point, I set a stone 13x12x10 ins., 9" in the ground, marked with 4 notches on E. and 1 notch on S. edges, from which  
An Oak 12" dia., bears N.60°E., 58 lks. dist. mkd. T30S R3W S28 BT.  
A Fir 18" dia., (24" now) bears S.70°W., 30 lks. dist. mkd. T30S R3W S32 BT. These marks are in the bark and being dim, I remark it in the wood T30S R3W S32 BT.  
A Laurel 10" dia., bears N.68°W., 46 lks. dist. mkd. T30S R3W S29 BT.  
The witness tree in sec. 33 is destroyed by fire. In its stead, I mark  
A Cedar 11" dia., bears S.69°E., 27 lks. dist. mkd. T30S R3W S33 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - June 9, 1960 - C.S. File 42/392-57

-----  
Determined by O.B.T.s:  
22" B.Oak snag N.60°E., 38.4 ft.  
26" Fir windfall, S.70°W., 19.8 ft., found scribe.  
24" Laurel N.82°W., 30.1 ft., found scribe.  
16" Cedar uproot, S.69°E., 17.8 ft.  
At corner point, found stone and set 3/4" x 30" iron pipe, from which  
30" laurel N.,70°W., 36.0 ft. "S29 T30S R3W BT."  
24" Cedar S.76°E., 27.0 ft. "S33 R3W BT."  
5" Fir S.55°E., 11.8 ft. "S28 BT."  
5" Chinquapin S.47°W., 9.7 ft. "S32 BT."

Fd. OK, April 1986 by W. Ruppert - C.S. File 63/36

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & 2008-1 thru 2008-4 Plats

-----  
The cor. of secs. 28, 29, 32, & 33, perpetuated by Markham in 1960, monumented with an iron pipe, 1" dia., firmly set, projecting 6" above the ground (alongside of which is the displaced orig. stone 12x10x20" with 3 notches on the east edge & 1 notch on the west edge) from which the remains of the orig. BTs

A roothole bears S.70°W., 19.8 ft. no trunk remains.

A burnt madrone stump, size indeterminate, bears N.82°W., 30.4 ft. with no marks visible. (Rec. N.68°W.)

and the remains of BTs mkd by Markham

A burnt cedar snag, size indeterminate, bears S.76°E., 27.0 ft. with no marks visible.

A burnt chinquapin stump, size indeterminate, bears S.47°W., 9.7 ft. with no marks visible.

A burnt madrone stump, size indeterminate, bears N.70°W., 36.0 ft. with no marks visible.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T30S	R3W
S 29	S 28
S 32	S 33
2004	

from which

A rebar, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.39½°E., 7.50 ft. with alum. cap mkd. RM T30S R3W S33 7.5 FT. TO COR. 2004 and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.38½°W., 7.50 ft. with alum. cap mkd. RM T30S R3W S32 7.5 FT. TO COR. 2004 and an arrow pointing to the cor.

Deposit a magnet in a white plastic case at the base & invert and bury the orig. stone along the north side of the stainless steel post.

Fd. & used on BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22515-6)

-----  
The geographic position (NAD 1983 (CORS 2002))  
Latitude: 42°55'52.52"N Longitude: 123°04'51.83"W