

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6959)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 16, 17, 20 and 21, marked T30S S16 on NE.; R3W S21 on SE.; S20 on SW. and S17 on NW. faces, with 4 notches on E. and 3 notches on S. edges, from which

A Fir 10" dia., bears N.61°E., 75½ lks. dist. mkd. T30S R3W S16 BT.

A Fir 32" dia., bears S.23½°E., 53 lks. dist. mkd. T30S R3W S21 BT.

A Fir 32" dia., bears S.30½°W., 71½ lks. dist. mkd. T30S R3W S20 BT.

A Laurel 12" dia., bears N.12¼°W., 35 lks. dist. mkd. T30S R3W S17 BT.

Survey by John H. Markham, Jr. - May 1952 - C.S. File 41/52-3

Set from O.B.T.:

30" dead Fir snag bears S.23½°E., 35.0 ft., found scribe and remarked "S21".

At corner, Set 1" x 30" Iron pipe, from which

36" Fir bears N.66°W., 111.0 ft. mkd. S17 BT.

23" Laurel bears N.66°E., 53.0 ft. mkd. S16 2880 T30S R3W BT.

5" Chinquapin bears S.52°W., 8.5 ft. mkd. S20 BT.

12" Maple bears S.49°W., 43.0 ft. mkd. S20 BT.

Corner lies on top of main ridge. Trail bears North 15.0'

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-11

Found - 1" I.Pipe.

12" Maple S.49°W., 43.0 ft., OK.

5" Chinquapin S.53°W., 85 ft., down.

23" Laurel N.66°E., 53.0 ft., OK.

36" Fir N.66°W., 111.0 ft., OK.

New BT - 26" Cedar S.82°E., 89.8 ft. scribed S21 T30S R3W CS BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #776, surveyed June/July 1972 - (DCSO records Vol. 36 Page(s) 14983-84)

The Sec. cor., perpetuated and recorded by Markham in 1952, monumented with an iron pipe 1" dia., firmly set, extending 6" above ground, from which the remains of the original bearing tree:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

A Fir 35" dia., bears S.23½°E., 53 lks. dist., with fragmentary scribe marks visible on opened blaze, and additional scribe marks S21 added by Markham, visible on bark.
and bearing trees marked by Markham:
A Madrone 23" dia., bears N.66°E., 80 lks. dist., with scribe marks S16 288 T30S R3W visible on bark.
A Maple 20" dia., bears S.49°W., 65 lks. dist., with healed blaze.
A Fir 50" dia., bears N.66°W., 167 lks., with healed blaze and a bearing tree mkd. by Byron in 1963:
A Cedar 26" dia., bears S.79°E., 137 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

| | |
|------|---------|
| T 30 | S R 3 W |
| S 17 | S 16 |
| S 20 | S 21 |
| 1972 | |

from which new bearing trees:
A Fir 7" dia., bears N.54°E., 71 lks. dist., mkd. T30S R3W S16 BT.
A Fir 7" dia., bears S.85°W., 128 lks. dist. mkd. T30S R3W S20 BT.
Reset iron pipe alongside iron post.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause
- Sept. 29, 1997 - C.S. 64/78-8

Found - 3½" brass cap on a 2½" O.D. iron pipe, protrudes 8" above ground. (1972)
1" I.D. iron pipe is a long SW'LY edge of BC/IP, protrudes 7" above ground.
32" now burnt and rotted D.Fir stump, no blazes or scribing visible, bears S.23½°E., 35' (agrees with rec.) 0BT.
36" now 42" dia 5' high D.Fir stump, with a healed blaze, bears N.66°W., 111' (agrees with 1952 & 1963 rec.) 1952.
23" now 32" dia. 1½' high Madrone stump, no blaze visible, bears N.67¼°E., 54.5' to center (rec. N.66°E., 53') 1952.
12" now 20" dia. Maple, no blaze visible, bears S.51°W., 44.4' (rec. S.49°W., 42.9') 1952.
26" now 42" dia. 2' high Cedar Stump, with a fully healed single blaze, bears S.79°E., 90.4' (agrees with 1972 rec.) 1963.
(Cont. Next page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

| | |
|---|--|
| New - | 7" now 12" dia. 2' high D.Fir stump, with a fully healed single blaze, bears N.54°E., 46.9' (agrees with rec.) 1972 7" now 9" dia. 20' high D.Fir snag, with a rotted burnt blaze no scribing visible, bears S.85°W., 84.5' (agrees with rec.) 1972. 5/8"x30" long I.R. with a DCSO alum. cap stamped "B 0 2 1997" protrudes 8" above ground, bears West, 57.7'. 5/8"x 30" long I.R. with a DCSO alum. cap stamped "B 0 1 1997" protrudes 8" above ground, bears North, 98.3'. Corner lies 25 ft. east of a ridge top road. Area burnt and logged around corner. |
| Greg Lang - Oct. 2004 - C.S. File 65/52-12 ----- | |
| Found - | 3½" BLM brass cap A 20" Maple bears S.49½°W., 44.00' (1952 Markham) A found 5/8" IR with a DCSO Aluminum cap bears N.00°42'W., 98.11' stamped "B 0 1 1997" |
| Set - | 5/8"x 36" IR/Aluminum cap bears N.89°41'E., 96.70' stamped "B 0 2 2004 LS 2295" 5½" D.Fir bears S.31½°W 13.10' scribed "S20 BT" 7" D.Fir bears N.83½°W 83.70' scribed "S 17 BT" |
| NOTE - | We set & measured to spikes in the base of all BTs; bearings to the trees are based on BLM's 1972 survey line from the N¼ Corner to the NW Section Corner of Section 21 (S.89°41'00"W). Corner lies on the top of a ridge & on the South side of a new rock road. |
| Fd. Ok by Greg Lang, 1/2007 - M152-13 | |
| Fd. & used on BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & Plat 2008-1 | |
| James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E ----- | |
| Found - | 3¼" brass cap stamped BLM, 1972 |
| BTs - | 9" Fir with tag dated 10/04 S.31½°W., 13.1' 24" Maple with tag dated 9-97, S.51°W., 44.4' 14" Fir with tag dated 10/04, N.83½°W., 83.7' |