

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6963)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S. on W. face, from which

A Cedar 10" dia., bears N.88 1/2°W., 25 lks. dist. mkd. 1/4 S BT.

A Chinquapin 6" dia., bears N.78°E., 26 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, Wm. Stoffel, Mike Darby, crew - June 1964 - C.S. File 52/138-52

-----  
Found - Stake at corner.

10" Cedar now 22" snag, N.88 1/2°W., 16.5 ft. Chopped open, found scribing "1/4 S"

6" Chinquapin N.78°E., 17.2 ft., not found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 3 W

1/4 S17 | S16

1964

New BTs- 6" Fir N.77°W., 22.0 ft. mkd. 1/4 S17 CS BT.

12" R.Cedar N.18°E., 65.2 ft. mkd. 1/4 S16 CS BT.

Greg Lang - Nov. 2004 - C.S. File 65/52-16A

-----  
Found - DCSO Brass cap

19" Cedar bears N.16 1/2°E., 64.4' (1964 by DCSO)

Fir stump bears N.77 1/2°W., 21.5' (1964 by DCSO)

New - 13" D.Fir bears S.83 1/2°E., 39.9' scribed "1/4 S16 BT"

17 1/2" D.Fir bears S.10 1/2°W., 56.2' scribed "1/4 S17 BT"

11" D.Fir bears N.23°W., 12.8' scribed "1/4 S17 BT"

Note - We set & measured to spikes in the base of all BTs; bearings to the trees are based on BLM's 1972 survey line from the N 1/4 Corner to the NW Sec. Corner of Sec 21 (S.89°41'00"W).

Corner is located on an easterly slope and on the east side of a gravel road; corner is also northerly of the same gravel road as said road proceeds to the south and east.

Fd. Ok by Greg Lang, 1/2007 - M152-13

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

-----  
Found - 2½" brass cap stamped County Surveyor Office 1964  
BTs - 15.3" Fir with tag dated 11/04 S.83½°E., 39.9' to  
nail side center  
19.4" snag with tag dated 11/04 S.10½°W., 56.2'  
13.6" Fir with tag dated 11/04 N.23°W., 12.8' to  
nail side center  
18" snag 4 ft. tall with tag dated 6/64 N.77°W.,  
22.0'

Ron Quimby - Crew: N. Fromdahl & R Vincent - 3/2019 - C.S.  
File 65/102-14

-----  
Found - DCSO brass cap (properly mkd)  
22" Cedar N.16½°E., 64.4 ft., good scar.  
15" Fir S.83½°E., 39.9 ft., good scar.  
19" Fir snag S.10½°W., 56.2 ft., good scar.  
14" Fir N.23°W., 12.8 ft., good scar.  
18" Fir stump N.77°W., 1.5 ft. good scar.  
New - 22" D.Fir S.3°W., 26.3 ft. scribed ¼ S17 BT.  
Note - Compass decl. 15½°E.