

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6963)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 8, 9, 16 and 17, marked T30S S9 on NE.; R3W S16 on SE.; S17 on SW.; and S8 on NW. faces, with 4 notches on E. and S. edges, from which

- A Fir 16" dia., bears N.15½°E., 53 lks. dist. mkd. T30S R3W S9 BT.
- A Maple 6" dia., bears S.17 3/4°E., 26¼ lks. dist. mkd. T30S R3W S16 BT.
- A Fir 11" dia., bears S.56¼°W., 30 lks. dist. mkd. T30S R3W S17 BT.
- A Fir 22" dia., bears N.13½°W., 49 lks. dist. mkd. T30S R3W S8 BT.

Survey by John H. Markham, Jr. - Wit: Bud Johnson; Fred Seymour; Wm. Markham - Oct. 4, 1951 - C.S. File 40/381-1

-----  
Determined by O.B.T.:

- A Fir 26" dia., bears N.13°W., 33.0 ft.
- A Fir 18" dia., bears N.15°E., 35.0 ft.
- A Fir 26" dia., bears S.56°W., 18.0 ft.

I remark the 3 original BTs.

At the corner point, Set 1" x 30" I.P., from which

- A Fir 13" dia., bears S.66°E., 53.2 ft. mkd. S16 BT.

Douglas Co. Surveyors Office - John M. Powell; Cliff Stone - Oct. 27, 1966 - C.S. File 54/52-5

-----  
Found - I.Pipe at sec. corner.

- Orig. 18" D.Fir now 24" N.15°E., 35.0 ft., shows good scar.
- Orig. 26" D.Fir now 31", S.56°W., 18.0 ft. (Dist. is 19.0 ft.), shows good old scar and bark scribe.
- Orig. 26" D.Fir now stump N.13°W., 33.0 ft. Stump has been opened.
- 13" D.Fir now snag, S.66°E., 53.2 ft., scribe visible.

Set brass cap alongside I.P. at cor. marked:

County Surveyors Office

T 30 S R 3 W

S 8 | S 9

S 17 | S 16

1966

New BT - 10" Cedar N.32°W., 8.5 ft. mkd. T30S R3W S8 CS BT  
No other trees available.

Corner lies NW. of cutting corner and in heavy reproduction.

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Bruce Shaner, PLS #430 - For: Longview Fibre and C & D Lumber - Aug. 23, 1979 - M 79-2

-----  
Found - 1966 DCS0 brass cap properly marked, from which  
28" D.Fir, orig. BT, with face, bears N.15½°E., 35.0  
ft.  
14" Cedar BT, scribes visible, bears N.32°W., 8.5 ft  
32" D.Fir, orig BT, old face and bark scribes, bears  
S.56¼°W., 19.0 ft. (Rec. 19.8 ft.)  
13" D.Fir, I scribe "T30S R3W S16 BT", bears  
S.66½°E., 32.0 ft.  
1" iron pipe adjacent to brass cap.

Greg Lang - For: Silver Butte Timber Co. - 1/2007 - M152-13

-----  
Found - Brass cap  
Existing 30½" D.Fir bears N.15½°E 35.0'  
Existing 15½" Cedar bears N.32°W., 8.5'  
New - 14" Fir bears S.34°27'W., 66.90' scribed "T30S R3W  
S17 BT"  
5/8"x30" iron rod bearing object with plastic cap  
mkd: "LANG SURVEYING" bears S.60°E., 32.70'

FD. Ok by Troy Rambo, 9/2007 - M154-22

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

-----  
Found - 2½" brass cap stamped County Surveyor Office 1966  
BTs - 31" Fir with tag dated 1/57 N.15°E., 35' to nail  
side center  
16.2" Fir with tag not marked S.40°W., not able to  
measure dist. due to steep slope and fallen trees  
BT has fallen down, tag dated 1/57 N.56°E., no  
distance given and not measured  
17.5" Cedar with set tag dated 09/07 N.25°W., 8.6'  
to nail side center