

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6966)

Set a stone 20 x 12 x 10 ins., 15" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Maple 11" dia., bears N.42½°E., 35 lks. dist mkd. ¼ S BT
A Cedar 12" dia., bears N.35¾°W., 16 lks. dist mkd. ¼ S BT

Survey by Bruce Shaner, PLS #430 - For: Longview Fiber Co. and C & D Lumber - Aug. 23, 1979 - M 79-2

Set brass cap mkd T30S R3W WM ¼ S8 S9 PLS 430 1979 from which
12" D.Fir, I scribe "¼ S9 BT" bears S.52°E., 19.2 ft.
10" D.Fir, I scribe "¼ S8 BT" bears S.72°W., 25.6 ft.
No original evidence found.

Fd. OK, June 1993 by G. Lang - M 123-14

Douglas Co. Surveyor's Office - Crew: Stephen J Flaue & Jeffery Lorsung - 9/11/2018 - C.S. File 67/45-20

Found -A 2" i.d. iron pipe by B.A. Shaner in 1979 firmly set, projecting 9" above the ground with a 2½" brass cap (Properly) mkd

BTs by Shaner in 1979:

A 29" x 3.5' tall D.Fir stump bears S.52°E., 19.2 ft. with a healed blaze.

A 15" x 6.5' tall D.Fir stump bears S.72°W., 25.6 ft. with a healed blaze .

New BTS- A 13" D.Fir bears, N.0½°E., 45.5 ft. scribed "¼ S9 CS" "BT"

A 17" madrone bears N.89¼°E., 55.2 ft. scribed "¼ S9", "CSBT".

A 5" D.Fir bears N.55½°W , 36 ft. scribed "X" "CSBT"

Note - All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown.

A K-tag was placed due west approximately 45 ft. from the monument along the access road.

COMPASS DECLINATION: 15°E.

GEODETIC COORDINATES

LATITUDE: 42°58'56.359"N. LONGITUDE: 123° 04' 52.067"W.

DATUM: NAD 83, Epoch 2010.00

SOURCE: Trimble GeoXT 6000

N 490,121.40 E 4,230,732.93